

**LIST OF THE APPLICABLE G.S.T. TARIFF RATES OF  
GOODS WHICH ARE USED IN CESC JURDICTION**

| SL.NO | ITEM NO. | ITEM DISCREPTION                                                                                   | GST TARIFF CODE | GST RATE |
|-------|----------|----------------------------------------------------------------------------------------------------|-----------------|----------|
|       | <b>1</b> | <b>Line Supports (POLES)</b>                                                                       |                 |          |
| 1     | 1.01     | RCC Pole - 9 MIT Long, 145 Eg WL                                                                   | 6810            | 18%      |
| 2     | 1.02     | RCC Pole - 9 Mtr Long, 150 E:g WL St) Section                                                      | 6810            | 18%      |
| 3     | 1.03     | RCC Pole - 8 Mir Long, 1lb Kg WL                                                                   | 6810            | 18%      |
| 4     | 1.04     | PCC Pole - 8 Mtr Long, 140 Kg WL                                                                   | 6810            | 18%      |
| 5     | 1.05     | PSCC Pole - 8 Mtr Long, 200 Kg WL                                                                  | 6810            | 18%      |
| 6     | 1.06     | PSCC Pole - 9 Mtr Long, 200 Kg WL                                                                  | 6810            | 18%      |
| 7     | 1.07     | PSCC Pole - 9 Mtr Long, 160 Kg WL in Transverse Direction & 136 Kg WL in Longitudinal Direction    | 6810            | 18%      |
| 8     | 1.08     | Pre - Stressed Tubular Spun Pole 11 Mtr Long -500Kg WL                                             | 6810            | 18%      |
| 9     | 1.09     | RCC Pole - 9.5 Mtr Long, 350 Kg WL for 33kV Lines                                                  | 6810            | 18%      |
| 10    | 1.10     | 1 I WTS Long PSC pole of working Load 365 Kg for intermediate poles only                           | 6810            | 18%      |
| 11    | 1.11     | 9 Mtr PSCC Pole with working load of 300Kg                                                         | 6810            | 18%      |
| 12    | 1.12     | Guy less poles                                                                                     | 7308            | 18%      |
| 13    | 1.13     | Strut pole made of released MS Rail pole or Tubular pole along with clamp fish plate, bolts & nuts | 7308            | 18%      |
| 14    | 1.14     | 11Mtrs Long pole made of I Beam (MS) section size 200x100inni 25.9 Kg/mtr                          | 7308            | 18%      |
| 15    | 1.15     | 11Mtrs Long pole made of I Beam (MS) section size 75x85nun 19.5 Kg/mtr                             | 7308            | 18%      |
|       | <b>2</b> | <b>Cross Arms (MS Ea, GI)</b>                                                                      |                 |          |
| 16    | 2.01     | 11kV Horizontal X Arms - Mild Steel (MS)                                                           | 7308            | 18%      |
| 17    | 2.02     | 11kV Horizontal X Arms - Galvanised Iron (01)                                                      | 7308            | 18%      |
| 18    | 2.03     | 11kV Special 3 Pin X Arm - MS                                                                      | 7308            | 18%      |
| 19    | 2.04     | 11kV Special 3 Pin X Arm - GI                                                                      | 7308            | 18%      |
| 20    | 2.05     | LT 4 Pin X Arms - MS                                                                               | 7308            | 18%      |
| 21    | 2.06     | LT 4 Pin X Arms - GI                                                                               | 7308            | 18%      |
| 22    | 2.07     | LT 2 Pin X Arms - MS                                                                               | 7308            | 18%      |
| 23    | 2.08     | LT 2 Pin X Arms - GI                                                                               | 7308            | 18%      |
| 24    | 2.09     | 2 Pin Cross Arm with pole clamp, bolt & nuts St. washers for RCC Pole - MS                         | 7318            | 18%      |
| 25    | 2.10     | 2 Pin Cross Arm with pole clamp, bolt & nuts & washers for RCC Pole - GI                           | 7318            | 18%      |
| 26    | 2.11     | 2 Pin Cross Arm with pole clamp, bolt & nuts & washers for PSC Pole - MS                           | 7318            | 18%      |
| 27    | 2.12     | 2 Pin Cross Arm with pole clamp, bolt & nuts & washers for PSC Pole - GI                           | 7318            | 18%      |
| 28    | 2.13     | 4 Pin Cross Arm with pole clamp, bolt & nuts & washers for RCC Pole - MS                           | 7318            | 18%      |
| 29    | 2.14     | 4 Pin Cross Arm with pole clamp, bolt & nuts & washers for FCC Pole - GI                           | 7318            | 18%      |
| 30    | 2.15     | 4 Pin Cross Arm with pole clamp, bolt & nuts & washers for PSC Pole - MS                           | 7318            | 18%      |

|    |      |                                                                                                         |      |     |
|----|------|---------------------------------------------------------------------------------------------------------|------|-----|
| 31 | 2.16 | 4 Pin Cross Arm with pole clamp, bolt & nuts & washers for PSC Pole - GI                                | 7318 | 18% |
| 32 | 2.17 | 11 kV Horizontal Cross Arm with single top support, clamp, Bolt & Nuts with washers for ROC Poles-MS    | 7318 | 18% |
| 33 | 2.18 | 11 kV Horizontal Cross Arm with single top support, clamp, Bolt & Nuts with washers for FCC Poles-GI    | 7318 | 18% |
| 34 | 2.19 | 11 kV Horizontal Cross Ann with single top support, clamp, Bolt & Nuts with washers for PSCC Poles - MS | 7318 | 18% |
| 35 | 2.20 | 11 kV Horizontal Cross Arm with single top support, clamp, Bolt & Nuts with washers for PSCC Poles - GI | 7318 | 18% |
| 36 | 2.21 | Special 3 Pin Cross Arm, clamp and Bolt & Nuts for RCC Poles - MS                                       | 7318 | 18% |
| 37 | 2.22 | Special 3 Pin Cross Arm, clamp and Bolt & Nuts for FCC Poles - GI                                       | 7318 | 18% |
| 38 | 2.23 | LT ST Support 50x6mm Flat - MS                                                                          | 7308 | 18% |
| 39 | 2.24 | LT ST Support 50x6mm Flat - GI                                                                          | 7308 | 18% |
| 40 | 2.25 | HT ST Support 50x6mm. Flat - MS                                                                         | 7308 | 18% |
| 41 | 2.26 | HT ST Support 50x6mm Flat - GI                                                                          | 7308 | 18% |
| 42 | 2.27 | Brace for LT 1pin X arm (600mm long) - MS                                                               | 7317 | 18% |
| 43 | 2.28 | Brace for LT 4pin X arm (600mm long) - GI                                                               | 7317 | 18% |
| 44 | 2.29 | Brace for 11 kV special 3pin X arm (900mm long) - MS                                                    | 7317 | 18% |
| 45 | 2.30 | Brace for 11 kV special Spin X arm (900mm long) - GI                                                    | 7317 | 18% |
| 46 | 2.31 | LT Cross arms for vertical Configuration - MS                                                           | 7318 | 18% |
| 47 | 2.32 | LT Cross arms for vertical Configuration - GI                                                           | 7318 | 18% |
| 48 | 2.33 | EG Stirrups (MS) with 01 wire lacing                                                                    | 7318 | 18% |
| 49 | 2.34 | Spiral Earth Electrode                                                                                  | 7213 | 18% |
|    |      |                                                                                                         |      |     |
|    |      | <b>3 SMC Line Materials</b>                                                                             |      |     |
| 50 | 3.01 | 11KV Cross arm with HT top support (glass reinforced hot pressed SMC compound)                          | 8546 | 18% |
|    |      |                                                                                                         |      |     |
|    |      | <b>4 Anticlimbing Device</b>                                                                            |      |     |
| 51 | 4.01 | Spike type GI About 3.0 Kg in weight                                                                    | 7317 | 18% |
| 52 | 4.02 | GI Barbed wire (12mtrs/Kg)                                                                              | 7312 | 18% |
|    |      |                                                                                                         |      |     |
|    |      | <b>5 Ciamps MS &amp; GI</b>                                                                             |      |     |
| 53 | 5.01 | FCC Pole clamp - MS                                                                                     | 7318 | 18% |
| 54 | 5.02 | FCC Pole clamp - GI                                                                                     | 7318 | 18% |
| 55 | 5.03 | PCC Pole clamp - MS                                                                                     | 7318 | 18% |
| 56 | 5.04 | PCC Pole clamp - GI                                                                                     | 7318 | 18% |
| 57 | 5.05 | PSCC Pole clamp - MS                                                                                    | 7318 | 18% |
| 58 | 5.06 | PSCC Pole clamp - GI                                                                                    | 7318 | 18% |
| 59 | 5.07 | PCC Pole clamp type A for LT X arm - MS                                                                 | 7318 | 18% |
| 60 | 5.08 | PCC Pole clamp type A for LT X arm - GI                                                                 | 7318 | 18% |
| 61 | 5.09 | FCC Pole clamp type A for X arm upto 1M from pole top - MS                                              | 7318 | 18% |
| 62 | 5.10 | PCC Pole clamp type A for X arm upto 1M from pole top - GI                                              | 7318 | 18% |
| 63 | 5.11 | Clamps for fixing MV Lamp control box, fuse box/St light fixture on rail pole - MS                      | 7318 | 18% |
| 64 | 5.12 | Guy clamp - MS                                                                                          | 7318 | 18% |

|                                              |       |                                                                 |      |     |
|----------------------------------------------|-------|-----------------------------------------------------------------|------|-----|
| 65                                           | 5.13  | Guy clamp - GI                                                  | 7318 | 18% |
| 66                                           | 5.14  | Turn buckle (GI)                                                | 7318 | 18% |
| 67                                           | 5.15  | Anchor Rod using 12mm rounds/Gut-Rod - MS                       | 7318 | 18% |
| 68                                           | 5.16  | Anchor Rod using 12mm rounds/Guy Rod - GI                       | 7318 | 18% |
| 69                                           | 5.17  | RCC pole type C clamp for GOS Operating Handle                  | 7318 | 18% |
| 70                                           | 5.18  | MS Fish Plate                                                   | 7318 | 18% |
| 71                                           | 5.19  | GI Fish Plate                                                   | 7318 | 18% |
| 72                                           | 5.20  | Strain Clamps, 3 Bolt type for 70/90 kN Disc Insulator          | 7318 | 18% |
| <b>6 Insulators</b>                          |       |                                                                 |      |     |
| 73                                           | 6.01  | 11kV Ceramic Pin Insulator (Shell only)                         | 8546 | 18% |
| 74                                           | 5.02  | 11kV GI Pin for 11kV Ceramic Shell Insulators                   | 8546 | 18% |
| 75                                           | 5.03  | 1.1kV Ceramic Pin Insulator (Shell only)                        | 8546 | 18% |
| 76                                           | 6.04  | 1.1kV GI Pin FOR 11kV Cermaic shell Insulator                   | 8546 | 18% |
| 77                                           | 6.05  | 1 1kV, 5KN Composite/Polymeric Pin Insulator(20mm dia FP Rod)   | 8546 | 18% |
| 78                                           | 6.06  | 11kV, 5KN Composite/Polymeric Pin Insulator(24mm dia FP Rod)    | 8546 | 18% |
| 79                                           | 6.07  | No.8 Strain Insulator                                           | 8546 | 18% |
| 80                                           | 6.08  | No.15 Strain Insulator                                          | 8546 | 18% |
| 81                                           | 6.09  | DISC Insulator 45kN                                             | 8546 | 18% |
| 82                                           | 6.10  | DISC Insulator 70kN, Ball & Socket type                         | 8546 | 18% |
| 83                                           | 6.11  | DISC Insulator 90kN, Ball & Socket type                         | 8546 | 18% |
| 84                                           | 6.12  | DISC Insulator 120101, Ball & Socket type                       | 8546 | 18% |
| 85                                           | 6.13  | 11kV Solid Core Insulator                                       | 8546 | 18% |
| 86                                           | 6.14  | 11kV Post Insulator                                             | 8546 | 18% |
| 87                                           | 6.15  | Silcon Rubber Composite Insulator/11kV 45kN Polymeric Insulator | 8546 | 18% |
| 88                                           | 6.16  | 11kV, 70kN Composite/Polymeric Insulator                        | 8546 | 18% |
| <b>7 Accessories for composite insulator</b> |       |                                                                 |      |     |
| 89                                           | 7.01  | Cross Arm Strap (MS)                                            | 7318 | 18% |
| 90                                           | 7.02  | Strain Clamp up to Rabbit ACSR                                  | 7318 | 18% |
| 91                                           | 7.03  | Strain Clamp for Coyote ACSR                                    | 7318 | 18% |
| <b>8 Conductor</b>                           |       |                                                                 |      |     |
| 92                                           | 8.01  | Weasel ACSR                                                     | 7604 | 18% |
| 93                                           | 8.02  | Rabbit. ACSR                                                    | 7604 | 18% |
| 94                                           | 8.03  | Coyote ACSR                                                     | 7604 | 18% |
| 95                                           | 8.04  | Lynx ACSR                                                       | 7604 | 18% |
| <b>9 Guy Wire 86 GI Wire</b>                 |       |                                                                 |      |     |
| 96                                           | 9.01  | 7/10 SWG Guy Wire                                               | 7312 | 18% |
| 97                                           | 9.02  | 8 SWG GI Wire                                                   | 7312 | 18% |
| 98                                           | 9.03  | 10 SWG GI Wire                                                  | 7312 | 18% |
| 99                                           | 9.04  | GI Barbed Wire 12 SWG                                           | 7312 | 18% |
| <b>10 PG Clamps</b>                          |       |                                                                 |      |     |
| 100                                          | 10.01 | PG clamps for Lynx ACSR                                         | 7318 | 18% |
| 101                                          | 10.02 | Coyote to Coyote                                                | 7318 | 18% |
| 102                                          | 10.03 | Rabbit to Rabbit                                                | 7318 | 18% |
| 103                                          | 10.04 | Weasel to Rabbit                                                | 7318 | 18% |
| 104                                          | 10.05 | Weasel to Weasel                                                | 7318 | 18% |
| 105                                          | 10.06 | Squirrel to Weasel                                              | 7318 | 18% |

|     |       |                                                                                                                 |      |     |
|-----|-------|-----------------------------------------------------------------------------------------------------------------|------|-----|
|     |       |                                                                                                                 |      |     |
|     |       | <b>11 PG Clams Rabbit to Insulated Wire</b>                                                                     |      |     |
| 106 | 11.01 | 95 Sqmm                                                                                                         | 7318 | 18% |
| 107 | 11.02 | 120 Sqmm                                                                                                        | 7318 | 18% |
| 108 | 11.03 | 150 Sqmm                                                                                                        | 7318 | 18% |
| 109 | 11.04 | 185 Sqmm                                                                                                        | 7318 | 18% |
| 110 | 11.05 | 240 Sqmm                                                                                                        | 7318 | 18% |
| 111 | 11.06 | T - Clamps for Rabbit conductor with hot dipped galvanized bolts, Nuts and Washers                              | 7318 | 18% |
| 112 | 11.07 | T - Clamps for Coyote conductor with hot dipped galvanized bolts, Nuts and Washers                              | 7318 | 18% |
| 113 | 11.08 | T - Clamps for Lynx to Lynx with hot dipped galvanized bolts, Nuts and Washers                                  | 7318 | 18% |
| 114 | 11.09 | Single Tension Clamp Suitable for Rabbit                                                                        | 7318 | 18% |
| 115 | 11.10 | Single Tension Clamp Suitable for Coyote                                                                        | 7318 | 18% |
| 116 | 11.11 | Pad Clamps for Rabbit ACSR                                                                                      | 7318 | 18% |
| 117 | 11.12 | Pad Clamps for Lynx ACSR                                                                                        | 7318 | 18% |
| 118 | 11.13 | Pad Clamps for Coyote ACSR                                                                                      | 7318 | 18% |
| 119 | 11.14 | C - Type wedge connector + 2 hole padle for Rabbit ACSR                                                         | 7318 | 18% |
| 120 | 11.15 | C - Type wedge connector + 2 hole padle for Coyote ACSR                                                         | 7318 | 18% |
| 121 | 11.16 | C - Type wedge connector + 4 hole padle for Coyote ACSR                                                         | 7318 | 18% |
| 122 | 11.17 | C - Type wedge connector + 2 hole padle for Lynx ACSR                                                           | 7318 | 18% |
| 123 | 11.18 | C - Type wedge connector + 4 hole padle for Lynx ACSR                                                           | 7318 | 18% |
|     |       |                                                                                                                 |      |     |
|     |       | <b>12 C - Type wedge connector</b>                                                                              |      |     |
| 124 | 12.01 | Rabbit to Rabbit ACSR                                                                                           | 7318 | 18% |
| 125 | 12.02 | Rabbit to Coyote ACSR                                                                                           | 7318 | 18% |
| 126 | 12.03 | Rabbit to Lynx ACSR                                                                                             | 7318 | 18% |
| 127 | 12.04 | Coyote to Coyote ACSR                                                                                           | 7318 | 18% |
| 128 | 12.05 | Rabbit to 240 Sqmm Lead Wire                                                                                    | 7318 | 18% |
| 129 | 12.06 | Coyote to 240 Sporn Lead Wire                                                                                   | 7318 | 18% |
| 130 | 12.07 | Coyote to Lynx ACSR                                                                                             | 7318 | 18% |
| 131 | 12.08 | Lynx to Lynx ACSR                                                                                               | 7318 | 18% |
| 132 | 12.09 | C wedge connector for connecting main wire of size 2.5/4/6/10 Sulu' from OH Squirrel/Weasel line to AFB/Cutouts | 7318 | 18% |
| 133 | 12.10 | C wedge connector for connecting main wire of size 16/25 Sqmm from OH Rabbit line to AFB/Cutouts                | 7318 | 18% |
|     |       |                                                                                                                 |      |     |
|     |       | <b>13 Distribution Transformers - 3 Phase, 11kV/433V - Stacked Core with Oil</b>                                |      |     |
| 134 |       | <b>A. OPEN BUSHING TYPE</b>                                                                                     |      |     |
| 135 | 13.01 | 15kVA, Copper Winding                                                                                           | 8504 | 18% |
| 136 | 13.02 | 25kVA, Aluminum Wdg (Conventional)                                                                              | 8504 | 18% |
| 137 | 13.03 | 25kVA, Aluminum_ Wdg, BEE 3 Star Rated                                                                          | 8504 | 18% |
| 138 | 13.04 | 25kVA, Aluminum Wdg, BEE 4 Star Rated                                                                           | 8504 | 18% |
| 139 | 13.05 | 63kVA, Aluminum Wdg                                                                                             | 8504 | 18% |
| 140 | 13.06 | 63kVA, Aluminum Wdg, BEE 3 Star Rated                                                                           | 8504 | 18% |

|     |       |                                                                                         |      |     |
|-----|-------|-----------------------------------------------------------------------------------------|------|-----|
| 141 | 13.07 | 63kVA, Aluminum Wdg, BEE 4 Star Rated                                                   | 8504 | 18% |
| 142 | 13.08 | 100kVA, Aluminum Wdg                                                                    | 8504 | 18% |
| 143 | 13.09 | 100kVA, Aluminium Wdg, BEE 3 Star Rated                                                 | 8504 | 18% |
| 144 | 13.10 | 100kVA, Aluminium Wdg, BEE 4 Star Rated                                                 | 8504 | 18% |
| 145 | 13.11 | 250kVA, Aluminum Wdg                                                                    | 8504 | 18% |
| 146 | 13.12 | 250kVA, BEE 3 Star Rated/Energy Efficient                                               | 8504 | 18% |
| 147 | 13.13 | 500kVA, Aluminum Wdg                                                                    | 8504 | 18% |
| 148 | 13.14 | 500kVA, BEE 3 star rated                                                                | 8504 | 18% |
| 149 | 13.15 | Special Design Transformer 354.2kVA for Niranthara Jyothi Works (11KV AUTO Transformer) | 8504 | 18% |
|     |       | <b>B. CABLE ENTRY TYPE</b>                                                              |      |     |
| 150 | 13.16 | 25kVA, Aluminum Wdg, BEE 3 Star Rated                                                   | 8504 | 18% |
| 151 | 13.17 | 25kVA, Aluminum Wdg, BEE 4 Star Rated                                                   | 8504 | 18% |
| 152 | 13.18 | 63kVA, Aluminum Wdg, BEE 3 Star Rated                                                   | 8504 | 18% |
| 153 | 13.19 | 63kVA, Aluminum Wdg, BEE 4 Star Rated                                                   | 8504 | 18% |
| 154 | 13.20 | 100kVA, Aluminium Wdg, BEE 3 Star Rated                                                 | 8504 | 18% |
| 155 | 13.21 | 100kVA, Aluminium Wdg, BEE 4 Star Rated                                                 | 8504 | 18% |
| 156 | 13.22 | 250kVA, Aluminum Wdg                                                                    | 8504 | 18% |
| 157 | 13.23 | 500kVA, Aluminum Wdg                                                                    | 8504 | 18% |
|     |       |                                                                                         |      |     |
| 14  |       | <b>Distribution Transformer - 3 Phase, 11k17/433V - Amorphous Core with Oil</b>         |      |     |
|     |       | <b>A. OPEN BUSHING TYPE</b>                                                             |      |     |
| 158 | 14.01 | 25kVA, BEE 3 Star Rated                                                                 | 8504 | 18% |
| 159 | 14.02 | 25kVA, BEE 5 Star Rated                                                                 | 8504 | 18% |
| 160 | 14.03 | 63kVA, BEE 3 Star Rated                                                                 | 8504 | 18% |
| 161 | 14.04 | 63kVA, BEE 5 Star Rated                                                                 | 8504 | 18% |
| 162 | 14.05 | 100kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
| 163 | 14.06 | 100kVA, BEE 5 Star Rated                                                                | 8504 | 18% |
| 164 | 14.07 | 200kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
| 165 | 14.08 | 500kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
|     |       |                                                                                         |      |     |
|     |       | <b>B. CABLE ENTRY TYPE</b>                                                              |      |     |
| 166 | 14.09 | 25kVA, BEE 3 Star Rated                                                                 | 8504 | 18% |
| 167 | 14.10 | 63kVA, BEE 3 Star Rated                                                                 | 8504 | 18% |
| 168 | 14.11 | 100kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
| 169 | 14.12 | 200kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
| 170 | 11.13 | 500kVA, BEE 3 Star Rated                                                                | 8504 | 18% |
|     |       |                                                                                         |      |     |
|     |       | <b>Distribution Transformer Self Protected 11kV/433V, 3 Phase</b>                       |      |     |
|     |       | <b>15 Protected 11kV/433V, 3 Phase</b>                                                  |      |     |
| 171 | 15.01 | 100 kVA                                                                                 | 8504 | 18% |
| 172 | 15.02 | 250 kVA                                                                                 | 8504 | 18% |
|     |       |                                                                                         |      |     |
|     |       | <b>16 DTs - Single Phase, 11kV/250V</b>                                                 |      |     |
| 173 | 16.01 | 15kVA, Copper Wound with MCCB                                                           | 8504 | 18% |
| 174 | 16.02 | 15kVA, Amorphous Core Copper Winding with MCCB                                          | 8504 | 18% |
| 175 | 16.03 | 10kVA, Copper winding with MCCB                                                         | 8504 | 18% |
|     |       |                                                                                         |      |     |

|     |       |                                                                                                                       |      |     |
|-----|-------|-----------------------------------------------------------------------------------------------------------------------|------|-----|
|     |       | <b>11kV/433V, 3 Phase, Dry Type</b>                                                                                   |      |     |
|     |       | <b>17 Transformers</b>                                                                                                |      |     |
| 176 | 17.01 | 25KVA                                                                                                                 | 8504 | 18% |
| 177 | 17.02 | 63INA                                                                                                                 | 8504 | 18% |
| 178 | 17.03 | 100KVA                                                                                                                | 8504 | 18% |
| 179 | 17.04 | 250KVA                                                                                                                | 8504 | 18% |
| 180 | 17.05 | 500KVA                                                                                                                | 8504 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>18 Transformer Oil</b>                                                                                             |      |     |
| 181 | 18.01 | EHV Grade Transformer oil - New                                                                                       | 2710 | 18% |
| 182 | 18.02 | Reclaimed oil                                                                                                         | 2710 | 18% |
| 183 | 18.03 | Contaminated oil                                                                                                      | 2710 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>19 LT Protection</b>                                                                                               |      |     |
| 184 | 19.01 | LT Protection kit                                                                                                     | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>20 LT Distribution Box</b>                                                                                         |      |     |
| 185 | 20.01 | LT Distribution Box for 100/250 WA DTC with MCCB's (Sheet Metal)                                                      | 8537 | 28% |
| 186 | 20.02 | LT Distribution Box for 100/250 kVA DTC with MCCB's (SMC)                                                             | 8537 | 28% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>21 LT Wirin kit for LT Protection kit</b>                                                                          |      |     |
| 187 | 21.01 | For 25 kVA DTC Single Circuit                                                                                         | 8535 | 18% |
| 188 | 21.02 | For 63 kVA DTC Single Circuit                                                                                         | 8535 | 18% |
| 189 | 21.03 | For 63 kVA DTC Double Circuit                                                                                         | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>22 LT Wiring kit through Distribution Box</b>                                                                      |      |     |
| 190 | 22.01 | For 100 kVA DTC Single Circuit                                                                                        | 8535 | 18% |
| 191 | 22.02 | For 100 kVA DTC Double Circuit                                                                                        | 8535 | 18% |
| 192 | 22.03 | For 250 kVA DTC Single Circuit                                                                                        | 8535 | 18% |
| 193 | 22.04 | For 2501:VA DTC Double Circuit                                                                                        | 8535 | 18% |
| 194 | 22.05 | LT Wiring kit for 63kVA Transformers (MESCOM Specification)                                                           | 8535 | 18% |
| 195 | 22.06 | LT Wiring kit for 25kVA Transformers (MESCOM Specification)                                                           | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>23 Lightning Arresters</b>                                                                                         |      |     |
| 196 | 23.01 | LA 9kV, 5kA, Metal Oxide                                                                                              | 8535 | 18% |
| 197 | 23.02 | IA 9kV, 5kA, Polymeric Type                                                                                           | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>24 HG Fuse Unit</b>                                                                                                |      |     |
| 198 | 24.01 | 11kV Class, HG Fuse Unit with Solid Core Insulators                                                                   | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>25 Double Pole TC Sets (Tap Changer)</b>                                                                           |      |     |
| 199 | 25.01 | For 25/63kVA Transformer - MS                                                                                         | 8481 | 18% |
| 200 | 25.02 | For 25/63kVA Transformer - GI                                                                                         | 8481 | 18% |
| 201 | 25.03 | For 25/63kVA Star Rated Transformer - MS                                                                              | 8481 | 18% |
| 202 | 25.04 | For 25/63kVA Star Rated Transformer - GI                                                                              | 8481 | 18% |
| 203 | 25.05 | For 100/300kVA Transformer - MS                                                                                       | 8481 | 18% |
| 204 | 25.06 | For 100/300kVA Transformer - GI                                                                                       | 8481 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>26 Single Pole Mounted Transformer Kit for 250kVA on 11 Mtr Spun Poles</b>                                         |      |     |
| 205 | 26.01 | Single H Frame with Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 25kVA (OH Line) - MS | 7308 | 18% |

|                                      |       |                                                                                                                                      |      |     |
|--------------------------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 206                                  | 26.02 | Single H Frame with Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 25kVA (OH Line) - GI                | 7308 | 18% |
| 207                                  | 26.03 | Three H Frame with Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 25kVA (UG Cable) - MS                | 7308 | 18% |
| 208                                  | 26.04 | Three H Frame with Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 25kVA (DO Cable) - GI                | 7308 | 18% |
| 209                                  | 26.05 | Single H Frame without Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 63/100/250/SOOkVA (OH Line) - MS | 7308 | 18% |
| 210                                  | 26.06 | Single H Frame without Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 63/100/250/500kVA (OH Line) - GI | 7308 | 18% |
| 211                                  | 26.07 | Three H Frame without Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 63/100/250/500kVA (UG Cable) - MS | 7308 | 18% |
| 212                                  | 26.08 | Three H Frame without Transformer Seating and Seating angle support X arm for 11 mtr Spun Pole for 63/100/250/500kVA (UG Cable) - GI | 7308 | 18% |
| <b>27 SPMT Materials</b>             |       |                                                                                                                                      |      |     |
| 213                                  | 27.01 | Single Pole Mounted Transformer kit for 25/63 kVA on 9 mtr RCC Poles (Square Section) - MS                                           | 7308 | 18% |
| 214                                  | 27.02 | Single Pole Mounted Transformer kit for 25/63 kVA on 9 mtr RCC Poles (Square Section) - GI                                           | 7308 | 18% |
|                                      |       | kVA on 9 mtr RCC Poles (Square Section) - GI                                                                                         | 7308 | 18% |
| 215                                  | 27.03 | Single Pole Mounted Transformer kit for 100 kVA on 9 mtr RCC Poles - MS                                                              | 7308 | 18% |
| 216                                  | 27.04 | Single Pole Mounted Transformer kit for 100 kVA on 9 mtr RCC Poles - GI                                                              | 7308 | 18% |
| 217                                  | 27.05 | Single Pole Mounted Transformer kit for 25 kVA on 9 mtr PSCC Poles of 300kG WL - MS                                                  | 7308 | 18% |
| 218                                  | 27.06 | Single Pole Mounted Transformer kit for 25 kVA on 9 mtr PSCC Poles or 300kG WL - GI                                                  | 7308 | 18% |
| <b>28 GOS (Gang Operated Switch)</b> |       |                                                                                                                                      |      |     |
| 219                                  | 28.01 | 11kV, 200Amps Single Break GOS                                                                                                       | 8536 | 18% |
| 220                                  | 28.02 | 11kV, 200Amps Single Break GOS(Modified for footpath free)                                                                           | 8536 | 18% |
| 221                                  | 28.03 | 11kV, 200Amps Single Break GOS, Vertically Operated                                                                                  | 8536 | 18% |
| 222                                  | 28.04 | 11kV, 400Amps Double Break GOS                                                                                                       | 8536 | 18% |
| 223                                  | 28.05 | H - Frame Set for 11kV, 200Amps Single Break GOS Mounting - MS                                                                       | 8536 | 18% |
| 224                                  | 28.06 | F1 - Frame Set for 11kV, 200Amps Single Break GOS Mounting - GI                                                                      | 8536 | 18% |
| 225                                  | 28.07 | Male and Female contacts with. B&N for 11 W 200A GOS (3 Male & 3 Female contacts each)                                               | 8536 | 18% |
| 226                                  | 28.08 | 11kV 400Amps Special Roaster GOS                                                                                                     | 8536 | 18% |

|     |       |                                                                                    |      |     |
|-----|-------|------------------------------------------------------------------------------------|------|-----|
| 227 | 28.09 | Insulated GOS Rods                                                                 | 8536 | 18% |
|     |       | <b>DOLO Cutouts (Direction of Loading Operation)</b>                               |      |     |
| 228 | 29.01 | 11W DOLO Cutouts Conventional to Erstwhile KEB Specification                       | 7308 | 18% |
| 229 | 29.02 | 11W DOLO Cutouts REC Specification                                                 | 7308 | 18% |
|     |       | <b>30 DP Sets (2 Pole Structure Kit)</b>                                           |      |     |
| 230 | 30.01 | DP Sets - MS                                                                       | 7308 | 18% |
| 231 | 30.02 | DP Sets - GI                                                                       | 7308 | 18% |
|     |       | <b>31 3 Pole Structure Kit</b>                                                     |      |     |
| 232 | 31.01 | 3 Pole Structure Material - MS                                                     | 7308 | 18% |
| 233 | 31.02 | 3 Pole Structure Material - GI                                                     | 7308 | 18% |
|     |       | <b>32 C-Type Wedge Connectors (Fired)</b>                                          |      |     |
| 234 | 32.01 | Rabbit to Rabbit ACSR                                                              | 8536 | 18% |
| 235 | 32.02 | Coyote to Coyote ACSR                                                              | 8536 | 18% |
| 236 | 32.03 | Rabbit to Coyote ACSR                                                              | 8536 | 18% |
|     |       | <b>33 H - Clamps</b>                                                               |      |     |
| 237 | 33.01 | Rabbit to Rabbit ACSR                                                              | 7308 | 18% |
| 238 | 33.02 | Coyote to Coyote ACSR                                                              | 7308 | 18% |
| 239 | 33.03 | Rabbit to Coyote ACSR                                                              | 7308 | 18% |
| 240 | 33.04 | Two Hole Paddle (Rabbit ACSR)                                                      | 7308 | 18% |
| 241 | 33.05 | Microwedge Connector                                                               | 7308 | 18% |
|     |       | <b>34 LT Feeder Piller Box</b>                                                     |      |     |
| 242 | 34.01 | LT Feeder Piller Box 8 Way with Cutouts                                            | 7310 | 18% |
| 243 | 34.02 | 1,T Feeder Piller Box 12 Way with Cutouts                                          | 7310 | 18% |
| 244 | 34.03 | Low Voltage Link Box - 2 Way                                                       | 7310 | 18% |
| 245 | 34.04 | LOW Voltage Link Box - 4 Way                                                       | 7310 | 18% |
|     |       | <b>35 LT Spacers</b>                                                               |      |     |
| 246 | 35.01 | LT Line Spacers (4 Wire)                                                           | 7318 | 18% |
| 247 | 35.02 | LT Line Spacers (2 Wire)                                                           | 7318 | 18% |
| 248 | 35.03 | LT Spacer for TC Wiring                                                            | 7318 | 18% |
|     |       | <b>Armoured XLPE insulated LT UG Cable 1.1kV Class as per specification</b>        |      |     |
| 249 | 36.01 | 6 Sqmm, 2 Core                                                                     | 8544 | 28% |
| 250 | 36.02 | 10 Sqmm, 2 Core                                                                    | 8544 | 28% |
| 251 | 36.03 | 10 Sqmm, 4 Core                                                                    | 8544 | 28% |
| 252 | 36.04 | 16 Sqmm, 2 Core                                                                    | 8544 | 28% |
| 253 | 36.05 | 16 Sqmm, 4 Core                                                                    | 8544 | 28% |
| 254 | 36.06 | 25 Sqmm, 2 Core                                                                    | 8544 | 28% |
| 255 | 36.07 | 25 Sqmm, 4 Core                                                                    | 8544 | 28% |
| 256 | 36.08 | 50 Sqmm, 4 Core                                                                    | 8544 | 28% |
| 257 | 36.09 | 70 Sqmm, 3.5 Core                                                                  | 8544 | 28% |
| 258 | 36.10 | 95 Sqmm, 3.5 Core                                                                  | 8544 | 28% |
| 259 | 36.11 | 120 Sqmm, 3.5 Core                                                                 | 8544 | 28% |
| 260 | 36.12 | 150 Sqmm, 3.5 Core                                                                 | 8544 | 28% |
| 261 | 36.13 | 185 Sqmm, 3.5 Core                                                                 | 8544 | 28% |
| 262 | 36.11 | 240 Sqmm, 3.5 Core                                                                 | 8544 | 28% |
| 263 | 36.15 | 400 Sqmm, 3,5 Core                                                                 | 8544 | 28% |
|     |       | <b>Compression type Aluminium Tubular in Line Connector for Aluminum Conductor</b> |      |     |
| 265 | 37.01 | 10 Sqmm                                                                            | 8536 | 18% |



|     |       |                                                                                             |      |     |
|-----|-------|---------------------------------------------------------------------------------------------|------|-----|
| 266 | 37.02 | 16 Sqmm                                                                                     | 8536 | 18% |
| 267 | 37.03 | 25 Sqmm                                                                                     | 8536 | 18% |
| 268 | 37.04 | 35 Sqmm                                                                                     | 8536 | 18% |
| 269 | 37.05 | 50 Sqmm                                                                                     | 8536 | 18% |
| 270 | 37.06 | 70 Sqmm                                                                                     | 8536 | 18% |
| 271 | 37.07 | 95 Sqmm                                                                                     | 8536 | 18% |
| 272 | 37.08 | 120 Sqmm                                                                                    | 8536 | 18% |
| 273 | 37.09 | 150 Sqmm                                                                                    | 8536 | 18% |
| 274 | 37.10 | 185 Sqmm                                                                                    | 8536 | 18% |
| 275 | 37.11 | 240 Sqmm                                                                                    | 8536 | 18% |
| 276 | 37.12 | 400 Sqmm                                                                                    | 8536 | 18% |
|     |       |                                                                                             |      |     |
|     |       | <b>Straight Through Jointing Kits<br/>Suitable for 1.1kV Class LT UG<br/>38 Cables</b>      |      |     |
|     |       | <b>Epoxy Type</b>                                                                           |      |     |
| 277 | 38.01 | 10 Sqmm, 2 Core                                                                             | 8544 | 18% |
| 278 | 38.02 | 10 Sqmm, 4 Core                                                                             | 8544 | 18% |
| 279 | 38.03 | 16 Sqmm, 2 Core                                                                             | 8544 | 18% |
| 280 | 38.04 | 16 Sqmm, 4 Core                                                                             | 8544 | 18% |
| 281 | 38.05 | 25 Sqmm, 2 Core                                                                             | 8544 | 18% |
| 282 | 38.06 | 25 Sqmm, 4 Core                                                                             | 8544 | 18% |
| 283 | 38.07 | 50 Sqmm, 4 Core                                                                             | 8544 | 18% |
| 284 | 38.08 | 70 Sqmm, 3.5/4 Core                                                                         | 8544 | 18% |
| 285 | 38.09 | 95 Sqmm, 3.5/4 Core                                                                         | 8544 | 18% |
| 286 | 38.10 | 120 Sqmm, 3.5/4 Core                                                                        | 8544 | 18% |
| 287 | 38.11 | 185 Sqmm, 3.5/4 Core                                                                        | 8544 | 18% |
| 288 | 38.12 | 240 Sqmm, 3.5/4 Core                                                                        | 8544 | 18% |
| 289 | 38.13 | 400 Sqmm 3.5/4 Core                                                                         | 8544 | 18% |
|     |       | <b>HS Type</b>                                                                              |      |     |
| 290 | 38.14 | up to 6 Sqmm                                                                                | 8544 | 18% |
| 291 | 38.15 | 10 to 16 Squint                                                                             | 8544 | 18% |
| 292 | 38.16 | 25 to 35 Sqmm                                                                               | 8544 | 18% |
| 293 | 38.17 | 50 to 95 Sqmm                                                                               | 8544 | 18% |
| 294 | 38.18 | 120 to 225 Sqmm                                                                             | 8544 | 18% |
| 295 | 38.19 | 240 to 300 Sqmm                                                                             | 8544 | 18% |
| 296 | 38.20 | 400 Sqmm                                                                                    | 8544 | 18% |
|     |       |                                                                                             |      |     |
|     |       | <b>Epoxy Terminating Kit (Pothead)<br/>39 suitable for 1.1kV Class LT UG Cables</b>         |      |     |
| 297 | 39.01 | Up to 4C x 50 Sqmm                                                                          | 8536 | 18% |
| 298 | 39.02 | 3.5 x 70/95/120 Sqmm                                                                        | 8536 | 18% |
| 299 | 39.03 | 3.5 x 150/185 Squint                                                                        | 8536 | 18% |
| 300 | 39.04 | 3.5 x 225/240/300 Sqmm                                                                      | 8536 | 18% |
| 301 | 39.05 | 3.5 x 400/500 Sqmm                                                                          | 8536 | 18% |
|     |       |                                                                                             |      |     |
|     |       |                                                                                             |      |     |
|     |       | <b>Cast Iron Terminating Kit (Pothead)<br/>Suitable for 1.1kV Class LT UG<br/>40 Cables</b> |      |     |
| 302 | 40.01 | 2.5 to 25 Sqmm                                                                              | 8536 | 18% |
| 303 | 40.02 | 35 to 95 Squat                                                                              | 8536 | 18% |
|     |       |                                                                                             |      |     |
|     |       | <b>11kV, 3 Core, XLPE HTUG Cable<br/>(FLAT Armoured)<br/>41</b>                             |      |     |
| 304 | 41.01 | 95 Swann                                                                                    | 8544 | 28% |
| 305 | 41.02 | 120 Sqmm                                                                                    | 8544 | 28% |
| 306 | 41.03 | 240 Sqmm                                                                                    | 8544 | 28% |
| 307 | 41.04 | 400 Sqmm                                                                                    | 8544 | 28% |
|     |       |                                                                                             |      |     |
|     |       | <b>11kV, 3 Core, XLPE HTUG Cable<br/>(ROUND Armoured)<br/>42</b>                            |      |     |
| 308 | 42.01 | 95 Sqmm                                                                                     | 8544 | 28% |
| 309 | 42.02 | 120 Sqmm                                                                                    | 8544 | 28% |

|     |       |                                                                                                                                                     |      |     |
|-----|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 310 | 42.03 | 240 Sqmm                                                                                                                                            | 8544 | 28% |
| 311 | 42.04 | 400 Sqmm                                                                                                                                            | 8544 | 28% |
| 312 | 42.05 | 11kV Cables Fault Locating Equipments                                                                                                               | 8544 | 28% |
|     |       |                                                                                                                                                     |      |     |
|     |       | <b>43 1.1kV, XLPE LTUG Cable</b>                                                                                                                    |      |     |
| 313 | 43.01 | 3.5C x 25 Sqmm                                                                                                                                      | 8544 | 28% |
| 314 | 43.02 | 3.5C x 95 Sqmm                                                                                                                                      | 8544 | 28% |
| 315 | 43.03 | 3.5C x 150 Sqmm                                                                                                                                     | 8544 | 28% |
| 316 | 43.04 | 3.5C x 185 Sqmm                                                                                                                                     | 8544 | 28% |
| 317 | 43.05 | 3.5C x 240 Sqmm                                                                                                                                     | 8544 | 28% |
|     |       |                                                                                                                                                     |      |     |
|     |       | <b>11kV Auto Reclosures and Sectionalizers with Remote Communication Facility</b>                                                                   |      |     |
|     |       | <b>44</b>                                                                                                                                           |      |     |
| 318 | 44.01 | 11kV, 630A, 12.5KA Auto reclosures with control pannel including necessary hardware structure protection system etc., as per specification (MESCOM) | 8536 | 18% |
| 319 | 41.02 | 11kV, 12.5KA Sectionalizer with control box having control logic with necessary hardware etc., as per specification (MESCOM)                        | 8536 | 18% |
| 320 | 44.03 | 11kV, 230V, 2 Phase, 300VA control transformer for providing auxiliary power                                                                        | 8536 | 18% |
| 321 | 44.04 | 11kV/\ 3/110V/1.3 1 Phase metering PT class -1, 100VA per Phase for measurement of voltage                                                          | 8536 | 18% |
| 322 | 44.05 | GSM modem with connecting cable for remote communicating capabilities                                                                               | 8517 | 18% |
| 323 | 44.06 | Fabrication & supply of structural steel including painting etc.,                                                                                   | 7308 | 18% |
| 324 | 44.07 | 9.6kV, 200A long duration porcelien housed Surge arrestors                                                                                          | 8536 | 18% |
|     |       |                                                                                                                                                     |      |     |
|     |       | <b>Conventional RMUs (VCB Type) DAS Compatable (Ring Main Unit)</b>                                                                                 |      |     |
|     |       | <b>45</b>                                                                                                                                           |      |     |
| 325 | 45.01 | 3 Way RMU, 201) + 1VL (One Incomer + One Breakers + One Outgoing) with DAS Specification                                                            | 8537 | 18% |
| 326 | 45.02 | 4 Way RMU, 201) + 2VL (One Incomer + Two Breakers + One Outgoing) with DAS Specification                                                            | 8537 | 18% |
| 327 | 45.03 | 5 Way RMU, 201) + 2VL (One Incomer + Two Breakers + One Outgoing) with DAS Specification                                                            | 8537 | 18% |
| 328 | 45.04 | 6 Way RMU, 201) + 4VL (One Incomer + Four Breakers + One Outgoing) with DAS Specification                                                           | 8537 | 18% |
| 329 | 45.05 | Single 1/C Panel with DAS Specification 5 Way RMU, 20D + 3V1... (One Incomer + Three                                                                | 8537 | 18% |
| 330 | 45.06 | Breakers + One Outgoing), 350MVA, 800Amps with Cu Busbar                                                                                            | 8537 | 18% |
| 331 | 45.07 | 5 Way RMU, 201) + 3VL (One Incomer + Three Breakers + One Outgoing), 350MVA, 800Amps with Al Busbar                                                 | 8537 | 18% |
| 332 | 45.08 | 4 Way RMU, 20D + 2VL (One Incomer + Two Breakers + One Outgoing)                                                                                    | 8537 | 18% |
| 333 | 45.09 | 3 Way RMU, 20D + 1VL (One Incomer + One Breakers + One Outgoing)                                                                                    | 8537 | 18% |

|     |       |                                                                                                             |      |     |
|-----|-------|-------------------------------------------------------------------------------------------------------------|------|-----|
|     |       |                                                                                                             |      |     |
|     |       | <b>46 Conventional RMUs OD</b>                                                                              |      |     |
| 334 | 46.01 | One Breaker (VL) Panel with Cu Busbar                                                                       | 8537 | 18% |
| 335 | 46.02 | One Breaker (VL) Panel with Al Busbar                                                                       | 8537 | 18% |
| 336 | 46.03 | 3 Way RMU, 200 + 1VL (One Incomer + One Breakers + One Outgoing), 350MVA, 800Amps with Cu Busbar            | 8537 | 18% |
| 337 | 46.04 | 3 Way RMU, 20D + 1VL (One Incomer + One Breakers + One Outgoing), 350MVA, 800Amps with Al Busbar            | 8537 | 18% |
| 338 | 46.05 | 3 Way RMU, 20D + 1VL (One Incomer + One Breakers + One Outgoing), 250MVA, 400Amps, VCB Type with Cu Busbar  | 8537 | 18% |
| 339 | 46.06 | 3 Way RMU, 201) + 1VL (One Incomer + One Breakers + One Outgoing), 250MVA, 400Amps, VCB Type with Al Busbar | 8537 | 18% |
| 340 | 46.07 | Retrofitting of MEI make oil switch type OD with VCB                                                        | 8537 | 18% |
|     |       |                                                                                                             |      |     |
|     |       | <b>47 Conventional RMU Spares (VCR Type)</b>                                                                |      |     |
| 311 | 47.01 | Bus Support Insulator with Stem                                                                             | 8537 | 18% |
| 342 | 47.02 | CTs Trom Bone Type, 11kV Class, 200 - 100/VA - 15, Class 5P - 10                                            | 8537 | 18% |
| 343 | 47.03 | CTs resin cast, 11kV Class, 400 - 200/5A, UA15, Class 5P - 10                                               | 8537 | 18% |
| 344 | 47.04 | Spout Grid Insulator Assembly (Back)                                                                        | 8537 | 18% |
| 345 | 47.05 | Spout Grid Insulator Assembly (Front)                                                                       | 8537 | 18% |
| 346 | 47.06 | PT Insulator (Spout) 3 Nos                                                                                  | 8537 | 18% |
| 347 | 47.07 | Shunt Trip Coil                                                                                             | 8537 | 18% |
| 348 | 47.08 | Closing Coil                                                                                                | 8537 | 18% |
| 349 | 47.09 | Plug Assembly for grid 800A, 6 Nos                                                                          | 8537 | 18% |
| 350 | 47.10 | Para Plast Compound                                                                                         | 8537 | 18% |
| 351 | 47.11 | PT Fuse(NT) 11kV/V3 Amps without Stem, VTF Type - 11                                                        | 8537 | 18% |
| 352 | 17.12 | Insulated Housing                                                                                           | 8537 | 18% |
| 353 | 47.13 | Switch Insulators Left/Right/Centre                                                                         | 8537 | 18% |
| 354 | 47.14 | Vacuum Interruptor 20kA                                                                                     | 8537 | 18% |
| 355 | 47.15 | Flower Contact                                                                                              | 8537 | 18% |
|     |       |                                                                                                             |      |     |
|     |       | <b>48 For Schneider make RMU</b>                                                                            |      |     |
| 356 | 48.01 | Tripping Coil                                                                                               | 8538 | 18% |
| 357 | 48.02 | VIP Relay                                                                                                   | 8535 | 18% |
| 358 | 48.03 | Live Cable Indicator                                                                                        | 8538 | 18% |
| 359 | 48.04 | 11KV Fault Passage Indicator for Overhead Line                                                              | 8538 | 18% |
|     |       |                                                                                                             |      |     |
|     |       | <b>49 Compact RMUs, (VCB/SF6 Type) with Al Busbar</b>                                                       |      |     |
| 360 | 49.01 | 3 Way RMU, 200 + 1VL, One Incomer 4- One Breaker + One Outgoing, 350MVA, 650Amps                            | 8535 | 18% |
| 361 | 49.02 | 4 Way RMU, 200 + 2VL (One Incomer + Two Breakers + One Outgoing), 350MVA, 650Amps                           | 8535 | 18% |
| 362 | 49.03 | 5 Way RMU, 200 + 3VL (One Incomer + Three Breakers + One Outgoing), 350MVA, 650Amps                         | 8535 | 18% |

|                                      |       |                                                                                       |      |     |
|--------------------------------------|-------|---------------------------------------------------------------------------------------|------|-----|
| 363                                  | 49.04 | 6 Way RMU, 200 + 4 VL (One Incomer + Four Breakers + One Outgoing), 350MVA, 650Amps   | 8535 | 18% |
| 364                                  | 49.05 | 100 for RMU                                                                           | 8535 | 18% |
| 365                                  | 49.06 | 1VL for 350MVA, 650Amps RMU                                                           | 8535 | 18% |
| <b>50 Load Break Switches</b>        |       |                                                                                       |      |     |
| 366                                  | 50.01 | Load Break Switches Only Without Panel                                                | 8535 | 18% |
| 367                                  | 50.02 | Load Break Switches with Panel                                                        | 8535 | 18% |
| 368                                  | 50.03 | 3 Way Load Break Switch                                                               | 8535 | 18% |
| <b>51 Aerial Bunched Cable (ABC)</b> |       |                                                                                       |      |     |
| 369                                  |       | <b>11kV, HT Aerial Bunched Cable</b>                                                  |      |     |
| 370                                  | 51.01 | 3x95+1x70 Sqmm (Bare/Insulated messenger wire)                                        | 8544 | 18% |
| 371                                  | 51.02 | 3x120+1x95 Sqmm (Bare/Insulated messenger wire)                                       | 8544 | 18% |
| <b>LT Aerial Bunched Cable</b>       |       |                                                                                       |      |     |
| 372                                  | 51.03 | 3x95+1x70+1x16 Sqmm Street light (Insulated messenger cum Neutral)                    | 8544 | 18% |
| 373                                  | 51.04 | 3x95+1x70+1x25 Sqmm Street light (Insulated messenger emu Neutral)                    | 8544 | 18% |
| 374                                  | 51.05 | 3x95+1x70+1x35 Sqmm Street light (Insulated messenger cum Neutral)                    | 8544 | 18% |
| <b>52 Covered. Conductor</b>         |       |                                                                                       |      |     |
| 375                                  | 52.01 | Covered Conductor                                                                     | 8544 | 18% |
| <b>53 Accessories for ABC Cables</b> |       |                                                                                       |      |     |
| 376                                  | 53.01 | Suspension clamp suitable for insulated Messsenger wire of size 25 to 95Sq mm         | 8538 | 18% |
| 377                                  | 53.02 | 11kV, AB Cable Straight time joint kit suitable for 95 Sqmm                           | 8538 | 18% |
| 378                                  | 53.03 | 11kV, AB Cable Straight thru' joint kit suitable for 95 Sqmm                          | 8538 | 18% |
| 379                                  | 53.04 | 11 kV, AB Cable Straight Bull' joint kit suitable for 120 Sqmm                        | 8538 | 18% |
| 380                                  | 53.05 | 11kV ABC - T Jointing kit 95 - 120 Sqmm                                               | 8538 | 18% |
| 381                                  | 53.06 | 11kV ABC Termination kit 95 - 120 Sqmm                                                | 8538 | 18% |
| 382                                  | 53.07 | Surge Arestor( for AB Cable)                                                          | 8538 | 18% |
| 383                                  | 53.08 | Ground Connection for Messenger Wire                                                  | 8538 | 18% |
| 384                                  | 53.09 | Anchor Sleeve for Messenger Wire                                                      | 8538 | 18% |
| 385                                  | 53.10 | Single Phase Distribution Box for 20 Connections(SMC)                                 | 8538 | 18% |
| 386                                  | 53.11 | Single Phase Distribution Box for 10 Connections(SMC/polycarbonate)                   | 8538 | 18% |
| 387                                  | 53.12 | Three Phase Distribution Box for 5 Connections(SMC/Polycarbonate)                     | 8538 | 18% |
| 388                                  | 53.13 | Three Phase Distribution Box for 6 Connections(SMC)                                   | 8538 | 18% |
| 389                                  | 53.14 | Piercing Connector Suitable for 16 Sqmm - 95 Sqmm AB Cable - Service Connections      | 8538 | 18% |
| 390                                  | 53.15 | Piercing Connector Suitable for 16 Sqmm - 95 Sqmm AB Cable - Street Light Connections | 8538 | 18% |
| 391                                  | 53.16 | Piercing Connector Suitable for 25 Sqmm - 95 Sqmm AB Cable - Main to Main Connections | 8538 | 18% |



|     |       |                                                                                                         |      |     |
|-----|-------|---------------------------------------------------------------------------------------------------------|------|-----|
|     |       | <b>Heat Shrinkable Outdoor Type Cable Termination Kit for XLPE Cable</b>                                |      |     |
| 422 | 54.07 | 3x95 Sqmm                                                                                               | 8538 | 18% |
| 423 | 54.08 | 3x240 Sqmm                                                                                              | 8538 | 18% |
| 424 | 54.09 | 3x400 Sqmm                                                                                              | 8538 | 18% |
|     |       | <b>Termination Kit for PILC Cable Heat Shrinkable Indoor Type Cable</b>                                 |      |     |
| 425 | 54.10 | 3x95 Sqmm                                                                                               | 8538 | 18% |
| 426 | 54.11 | 3x240 Sqmm                                                                                              | 8538 | 18% |
| 427 | 54.12 | 3x400 Sqmm                                                                                              | 8538 | 18% |
|     |       | <b>Heat Shrinkable Outdoor Type Cable Termination Kit for PILC Cable</b>                                |      |     |
| 428 | 54.13 | 3x95 Sqmm                                                                                               | 8538 | 18% |
| 429 | 54.14 | 3x240 Sqmm                                                                                              | 8538 | 18% |
| 430 | 54.15 | 3x400 Sqmm                                                                                              | 8538 | 18% |
|     |       | <b>Heat Shrinkable Straight Through Jointing Kits for XLPE Cable with Copper Lugs &amp; Al Ferrules</b> |      |     |
| 431 | 54.16 | 3x95 Sqmm                                                                                               | 8538 | 18% |
| 432 | 54.17 | 3x240 Sqmm                                                                                              | 8538 | 18% |
| 433 | 54.18 | 3x400 Sqmm                                                                                              | 8538 | 18% |
|     |       | <b>Heat Shrinkable Straight Through Jointing Kits for PILC Cable with Copper Lugs &amp; Al Ferrules</b> |      |     |
| 434 | 54.19 | 3x95 Sqmm                                                                                               | 8538 | 18% |
| 435 | 54.20 | 3x240 Sqmm                                                                                              | 8538 | 18% |
| 436 | 54.21 | 3x400 Sqmm                                                                                              | 8538 | 18% |
|     |       | <b>55 Service Connection Accessories</b>                                                                |      |     |
| 437 | 55.01 | Pole Mounted Fibre Glass Reinforced Aerial Fuse Board 60Amps - 3 Way                                    | 8535 | 18% |
| 438 | 55.02 | Pole Mounted Fibre Glass Reinforced Aerial Fuse Board 30Amps - 3 Way                                    | 8535 | 18% |
| 439 | 55.03 | FGRP Aerial Fuse Boards 30Amps - 9 Way                                                                  | 8535 | 18% |
| 440 | 55.04 | FGRP Aerial Fuse Boards 30Amps - 5 Way                                                                  | 8535 | 18% |
| 441 | 55.05 | FGRP Aerial Fuse Boards 30Amps - 6 Way                                                                  | 8535 | 18% |
|     |       | <b>56 LT Service Connector</b>                                                                          |      |     |
| 442 | 56.01 | For Weasel                                                                                              | 8535 | 18% |
| 443 | 56.02 | For Rabbit                                                                                              | 8535 | 18% |
|     |       | <b>57 PVC Pipes</b>                                                                                     |      |     |
|     |       | <b>A. Pipes</b>                                                                                         |      |     |
| 444 | 57.01 | PVC Pipe - 20 mm Dia                                                                                    | 3917 | 18% |
| 445 | 57.02 | PVC Pipe - 25 mm Dia                                                                                    | 3917 | 18% |
| 446 | 57.03 | PVC Pipe - 32 mm Dia                                                                                    | 3917 | 18% |
| 447 | 57.04 | PVC Pipe - 40 mm Dia                                                                                    | 3917 | 18% |
| 448 | 57.05 | PVC Pipe - 50 mm Dia                                                                                    | 3917 | 18% |
| 449 | 57.06 | PVC Pipe - 63 mm Dia                                                                                    | 3917 | 18% |
| 450 | 57.07 | PVC Pipe - 75 mm Dia                                                                                    | 3917 | 18% |
| 451 | 57.08 | PVC Pipe - 80 mm Dia                                                                                    | 3917 | 18% |
| 452 | 57.09 | PVC Pipe - 100 mm Dia                                                                                   | 3917 | 18% |
| 153 | 57.10 | PVC Pipe - 150 mm Dia                                                                                   | 3917 | 18% |
| 454 | 57.11 | PVC Pipe - 200 mm Dia                                                                                   | 3917 | 18% |

|     |       |                                                                     |      |     |
|-----|-------|---------------------------------------------------------------------|------|-----|
|     |       | <b>B. Bends</b>                                                     |      |     |
| 455 | 57.12 | PVC Bend - 20 mm Dia                                                | 3917 | 18% |
| 456 | 57.13 | PVC Bend - 25 mm Dia                                                | 3917 | 18% |
| 457 | 57.14 | PVC Bend - 32 mm Dia                                                | 3917 | 18% |
| 458 | 57.15 | PVC Bend - 40 mm Dia                                                | 3917 | 18% |
| 959 | 57.16 | PVC Bend - 50 mm Dia                                                | 3917 | 18% |
| 460 | 57.17 | PVC Bend - 63 mm Dia                                                | 3917 | 18% |
| 461 | 57.18 | PVC Bend - 75 mm Dia                                                | 3917 | 18% |
| 462 | 57.19 | PVC Bend - 80 mm Dia                                                | 3917 | 18% |
| 463 | 57.20 | PVC Bend - 100 mm Dia                                               | 3917 | 18% |
| 464 | 57.21 | PVC Bend - 150 mm Dia                                               | 3917 | 18% |
| 465 | 57.22 | PVC Bend - 200 mm Dia                                               | 3917 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>58 GI Pipes B - Class</b>                                        |      |     |
| 466 | 58.01 | GI Pipe - 20 mm Dia                                                 | 7303 | 18% |
| 467 | 58.02 | GI Pipe - 25 mm Dia                                                 | 7303 | 18% |
| 468 | 58.03 | GI Pipe - 32 mm Dia                                                 | 7303 | 18% |
| 469 | 58.01 | GI Pipe - 40 mm Dia                                                 | 7303 | 18% |
| 470 | 58.05 | GI Pipe - 50 mm Dia                                                 | 7303 | 18% |
| 471 | 58.06 | GI Pipe - 63 mm Dia                                                 | 7303 | 18% |
| 472 | 58.07 | GI Pipe - 65 mm Dia                                                 | 7303 | 18% |
| 473 | 58.08 | GI Pipe - 100 mm Dia                                                | 7303 | 18% |
| 174 | 58.09 | GI Pipe - 150 mm Dia                                                | 7303 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>PVC Insulated &amp; Sheathed Aluminium Wires, Single Core</b>    |      |     |
|     |       | <b>59 Multistrand 1.1 kV Class</b>                                  |      |     |
| 475 | 59.01 | PVC Wire - 2.5 Sqmm                                                 | 7605 | 18% |
| 476 | 59.02 | PVC Wire - 1 Sqmm                                                   | 7605 | 18% |
| 477 | 59.03 | PVC Wire - 6 Sqmm                                                   | 7605 | 18% |
| 478 | 59.04 | PVC Wire - 10 Sqmm                                                  | 7605 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>PVC Insulated &amp; Un-Sheathed Aluminium Wires, Single Core</b> |      |     |
|     |       | <b>60 Multistrand. 1.1 kV class</b>                                 |      |     |
| 479 | 60.01 | PVC Wire - 16 Sqmm                                                  | 7605 | 18% |
| 480 | 60.02 | PVC Wire - 25 Sqmm                                                  | 7605 | 18% |
| 481 | 60.03 | PVC Wire - 35 Sqmm                                                  | 7605 | 18% |
| 482 | 60.04 | PVC Wire - 50 Sqmm                                                  | 7605 | 18% |
| 483 | 60.05 | PVC Wire - 70 Sqmm                                                  | 7605 | 18% |
| 484 | 60.06 | PVC Wire - 95 Sqmm                                                  | 7605 | 18% |
| 485 | 60.07 | PVC Wire - 120 Sqmm                                                 | 7605 | 18% |
| 486 | 60.08 | PVC Wire - 150 Sqmm                                                 | 7605 | 18% |
| 487 | 60.09 | PVC Wire - 185 Sqmm                                                 | 7605 | 18% |
| 488 | 60.10 | PVC Wire - 240 Sqmm                                                 | 7605 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>61 Fuse Wires</b>                                                |      |     |
| 489 | 51.01 | Tinned Copper Fuse Wire, 5A                                         | 7413 | 18% |
| 490 | 61.02 | Tinned Copper Fuse Wire, 10A                                        | 7413 | 18% |
| 491 | 61.03 | Tinned Copper Fuse Wire, 20A                                        | 7413 | 18% |
| 492 | 61.04 | Tinned Copper Fuse Wire, 100A                                       | 7413 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>62 Porcelain cut outs (500 Volts)</b>                            |      |     |
| 493 | 62.01 | 15/16A                                                              | 8546 | 18% |
| 494 | 62.02 | 30/32A                                                              | 8546 | 18% |
| 195 | 62.03 | 60/63A                                                              | 8546 | 18% |
| 496 | 62.01 | 100A                                                                | 8546 | 18% |
| 497 | 62.05 | 200A                                                                | 8546 | 18% |
| 498 | 62.06 | 300A                                                                | 8546 | 18% |
|     |       |                                                                     |      |     |
|     |       | <b>Grounding Materials for RMUs &amp; Transformers</b>              |      |     |
|     |       | <b>65 Pipe Grounding</b>                                            |      |     |

|     |       |                                                                                                                                                                                                                                                  |      |     |
|-----|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 499 | 65.01 | GI Grounding pipe, B - Class, 40mm dia, 2.Smtrs long, 2.9mm thick with bolts nuts, GI Strips and washers complete                                                                                                                                | 7303 | 18% |
| 500 | 65.02 | GI Grounding pipe, B - Class, 40mm dia, 2.Smtrs long, 3.2mm thick with bolts nuts, GI Strips and washers complete                                                                                                                                | 7303 | 18% |
| 501 | 65.03 | Good Quality well burnt Charcoal for grounding purposes packed in non returnable gunny bags of 30kg each                                                                                                                                         | 7303 | 18% |
| 502 | 65.04 | Good Quality Salt for grounding purposes packed 50kg gunny bags                                                                                                                                                                                  | 7303 | 18% |
|     |       |                                                                                                                                                                                                                                                  |      |     |
|     |       | <b>Rod Earthing</b>                                                                                                                                                                                                                              |      |     |
| 503 | 65.04 | Rod type of earthing using 40mm dia, 3mtr long MS rod as ground rod, in earth pit of 300mm width and 3300mm depth and using 50x6mm flat welded to ground rod as terminal equipment ground terminal using pvc Al wire as & connected to specified | 7215 | 18% |
| 504 | 65.05 | Bentonite clay slurry for earthing in 50 kg bags                                                                                                                                                                                                 | 2508 | 5%  |
|     |       |                                                                                                                                                                                                                                                  |      |     |
|     |       | <b>66 Alkathine tube</b>                                                                                                                                                                                                                         |      |     |
| 505 | 66.01 | Transparent Alkathine tube 19mm dia, 2mm thick m coils of 30 mfrs                                                                                                                                                                                | 3917 | 18% |
|     |       |                                                                                                                                                                                                                                                  |      |     |
|     |       | <b>67 Measuring Equipments</b>                                                                                                                                                                                                                   |      |     |
| 506 | 67.01 | High precision Single phase Electromechanicalmeters with magnetic suspension 2.5 - 10A, Class 2 accuracy                                                                                                                                         | 9028 | 18% |
| 507 | 67.02 | High precision 3 phase Electromechanical meters with magnetic suspension 5-20A, Class-2 accuracy                                                                                                                                                 | 9028 | 18% |
| 508 | 67.03 | LT Electronic Tri - Vector Meter 5A, Class-0.5/1.0 accuracy                                                                                                                                                                                      | 9028 | 18% |
| 509 | 67.04 | LT Electronic Tri - Vector Meter 5A, Class-0.5                                                                                                                                                                                                   | 9028 | 18% |
| 510 | 67.05 | HT Electronic Tri - Vector Meter 5A, Class-0.5 accuracy                                                                                                                                                                                          | 9028 | 18% |
| 511 | 67.06 | HT Electronic Tri - Vector Meter 5A, Class-0.2 accuracy with ABT features                                                                                                                                                                        | 9028 | 18% |
| 512 | 67.07 | Electronic Meter, 5- 10A/5-20A, SPb Class-1 Accuracy                                                                                                                                                                                             | 9028 | 18% |
| 513 | 67.08 | LT Single phase 5-30A, DLMS complaint static energy meter, class-1.0 Accuracy                                                                                                                                                                    | 9028 | 18% |
| 514 | 67.09 | Electronic Meter, 2.5-10A/5-20A, 3 Ph Class-1 Accuracy                                                                                                                                                                                           | 9028 | 18% |
| 515 | 67.10 | LT AC Three Phase 4 wire, 5-30A Static whole unidirectional complaint energy meter, Class — 1.0 Accuracy                                                                                                                                         | 9028 | 18% |
| 516 | 67.11 | Electronic Meter, 10-40A, 3 Ph Class-1 Accuracy                                                                                                                                                                                                  | 9028 | 18% |
| 517 | 67.12 | LT Three phase, 4wire, CT Operated DLMS complaint ETV meter-/5, class 05s Accuracy                                                                                                                                                               | 9028 | 18% |
| 518 | 67.13 | Electronic Meter, 5-20/30A, 3 Ph 4 wire Class - 1 Accuracy (whole current)                                                                                                                                                                       | 9028 | 18% |
| 519 | 67.14 | Electronic Meter, 10-40/60A, 3 Ph Class-1 Accuracy (whole current)                                                                                                                                                                               | 9028 | 18% |



|     |       |                                                                                                                                                                                                                                      |      |     |
|-----|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 520 | 67.15 | Electromechanical Energy Meter - 3 Ph, 3-20A, Class-2 Accuracy, for IP Sets                                                                                                                                                          | 9028 | 18% |
| 521 | 67.16 | LT, S.Ph, 5-30 A Static Energy Meter of Accuracy <b>Class in retail out lets of BESCO</b>                                                                                                                                            | 9028 | 18% |
| 522 | 67.17 | Pre - paid Energy meter single phase, 5-30A                                                                                                                                                                                          | 9028 | 18% |
| 523 | 67.18 | Pre - paid Energy meter three phase, 5-30A                                                                                                                                                                                           | 9028 | 18% |
| 524 | 67.19 | 3 phase 4 wire static meter (CT, PT operated) 3 x 63.5 V, 5 Amps or 1 Amps class 0.2s with Rs -485 & ABT features                                                                                                                    | 9028 | 18% |
| 525 | 67.20 | LT Three phase Four Wire 5-30A Thread through type composite Meter Housing Box consisting of ETV Meter with AMR comply and LTCT with built in GSM/GPRS modem (as per technical specification ) upto 100kVA Distribution Transformer. | 9028 | 18% |
| 526 | 67.21 | Numerical Over Current & Earth Fault Protecion Relay with Accessories                                                                                                                                                                | 9028 | 18% |
|     |       |                                                                                                                                                                                                                                      |      |     |
|     |       | <b>68 Meter Protection/Tamper Proof Boxes (MS) for LT Installations above 40 HP</b>                                                                                                                                                  |      |     |
| 527 | 68.01 | Meter Protection/Tamper Proof box with lumbar, for LT 3 Ph with CT Ratio 50/5A, Class-1 Accuracy                                                                                                                                     | 8535 | 18% |
| 528 | 68.02 | Meter Protection/Tamper Proof box with busbar, for LT 3 Ph with CT Ratio 75/5A, Class-1 Accuracy                                                                                                                                     | 8535 | 18% |
| 529 | 68.03 | Meter Protection/Tamper Proof box with busbar, for LT 3 Ph with CT Ratio 100/5A, Class-1 Accuracy                                                                                                                                    | 8535 | 18% |
| 530 | 68.04 | LT Metering Box for housing the ETV Meters without CT's busbar wiring etc;                                                                                                                                                           | 8535 | 18% |
| 531 | 68.05 | Pilfer proof box for below 40HP Installations                                                                                                                                                                                        | 8535 | 18% |
| 532 | 68.06 | SMC Meter protection box                                                                                                                                                                                                             | 8535 | 18% |
| 533 | 68.07 | LT SMC Metering box without CTs with wiring arrangement Modems compatible for DLMS meters with RS232 for LT installation                                                                                                             | 8535 | 18% |
| 534 | 68.08 | SMC Street Lighting Metering Box with Automatic Control Swith, Contactors with Single Phase 5-30 Amps meter & 50/5A CT                                                                                                               | 8535 | 18% |
| 535 | 68.09 | Numerical Poly Carbonate Seals                                                                                                                                                                                                       | 3926 | 28% |
| 536 | 68.10 | Meter Sealing Wire                                                                                                                                                                                                                   | 7217 | 18% |
| 537 | 68.11 | High security label seal                                                                                                                                                                                                             | 3919 | 18% |
| 538 | 68.12 | Poly carbonate sealing bits with out number                                                                                                                                                                                          | 3926 | 28% |
|     |       |                                                                                                                                                                                                                                      |      |     |
|     |       | <b>69 LT Current Transformers</b>                                                                                                                                                                                                    |      |     |
| 539 | 69.01 | CT Ratio - 25/5A, Class-1 Accuracy, 3.75 VA, Ring type                                                                                                                                                                               | 8504 | 18% |
| 540 | 69.02 | CT Ratio - 30/5A, Class-1 Accuracy, 3.75 VA, Ring type                                                                                                                                                                               | 8504 | 18% |
| 541 | 69.03 | CT Ratio - 50/5A, Class-1 Accuracy, 3.75 VA, Ring type                                                                                                                                                                               | 8504 | 18% |
| 542 | 69.04 | CT Ratio - 75/5A, Class-1 Accuracy, 3.75 VA, Ring type                                                                                                                                                                               | 8504 | 18% |

|     |       |                                                                                                   |      |     |
|-----|-------|---------------------------------------------------------------------------------------------------|------|-----|
| 543 | 69.05 | CT Ratio - 50/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                       | 8504 | 18% |
| 544 | 69.06 | CT Ratio - 75/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                       | 8504 | 18% |
| 515 | 69.07 | CT Ratio - 100/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                      | 8504 | 18% |
| 546 | 69.08 | CT Ratio - 150/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                      | 8504 | 18% |
| 547 | 69.09 | CT Ratio - 200/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                      | 8504 | 18% |
| 548 | 69.10 | CT Ratio - 300/5A, Class-0.5 Accuracy,<br>3.75VA, Ring type                                       | 8504 | 18% |
| 549 | 69.11 | CT Ratio - 400/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                      | 8504 | 18% |
| 550 | 69.12 | CT Ratio - 600/5A, Class-0.5 Accuracy,<br>3.75VA, Ring type                                       | 8504 | 18% |
| 551 | 69.13 | CT Ratio - 800/5A, Class-0.5 Accuracy,<br>3.75 VA, Ring type                                      | 8504 | 18% |
|     |       |                                                                                                   |      |     |
|     |       | <b>Instrument Transformers (PTs &amp;<br/>70 CTs) 11KV PTs</b>                                    |      |     |
| 552 | 70.01 | PT 11kV/ 110V, 50VA, Insulation level<br>15/35/95 kV as per IS 3156, Accuracy<br>class 0.5        | 8504 | 18% |
| 553 | 70.02 | PT 11KV/rt3/110V/rt3, 25VA,<br>Insulation level 15/35/95 kV as per IS<br>3156, Accuracy class 0.2 | 8504 | 18% |
| 554 | 70.03 | PT 11kV Station Type                                                                              | 8504 | 18% |
|     |       |                                                                                                   |      |     |
|     |       | <b>11KV CTs (Secondary -5A1 for 3<br/>71 phase-3 wire Metering)</b>                               |      |     |
| 555 | 71.01 | CT - 11kV, 2.5/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 556 | 71.02 | CT - 11kV, 5/5A, Accuracy Class 0.5                                                               | 9028 | 18% |
| 557 | 71.03 | CT - 11kV, 7.5/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 558 | 71.04 | CT - 11kV, 10/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 559 | 71.05 | CT - 11kV, 12.5/5A, Accuracy Class 0.5                                                            | 9028 | 18% |
| 560 | 71.06 | CT - 11kV, 15/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 561 | 71.07 | CT - 11kV, 20/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 562 | 71.08 | CT - 11kV, 25/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 563 | 71.09 | CT - 11kV, 30/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 564 | 71.10 | CT - 11kV, 40/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 565 | 71.11 | CT - 11kV, 50/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 566 | 71.12 | CT - 11kV, 60/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 567 | 71.13 | CT - 11kV, 75/5A, Accuracy Class 0.5                                                              | 9028 | 18% |
| 568 | 71.14 | CT - 11kV, 100/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 569 | 71.15 | CT - 11kV, 150/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 570 | 71.16 | CT - 11kV, 200/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 571 | 71.17 | CT - 11kV, 400/5A, Accuracy Class 0.5                                                             | 9028 | 18% |
| 572 | 71.18 | 11 KV CTs (Secondary 1A)                                                                          | 9028 | 18% |
| 573 | 71.19 | CT-11KV, 1.25/1A to 2.5/1A,<br>Burden:2.5VA Accuracy Class 0.2                                    | 9028 | 18% |
| 574 | 71.20 | CT-11KV, 5/1A to 100/1A,<br>Burden:2.5VA Accuracy Class 0.2                                       | 9028 | 18% |
| 575 | 71.21 | CT-11KV, 125/ 1A to 200/1A,<br>Burden:2.5VA Accuracy Class 0.2                                    | 9028 | 18% |
| 576 | 71.22 | CT-11KV, 225/ 1A to 400/1A,<br>Burden:2.5VA Accuracy Class 0.2                                    | 9028 | 18% |

|     |           |                                                                                                                                                                                                                                   |      |     |
|-----|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
|     | <b>72</b> | <b>HT Metering Equipments</b>                                                                                                                                                                                                     |      |     |
|     |           | <b>HT Metering cubicle, 11kV Class, All single ratio CTs including ETV Meter (2CT 2PT)</b>                                                                                                                                        |      |     |
| 577 | 72.01     | Without Load Break Switch                                                                                                                                                                                                         | 8535 | 18% |
| 578 | 72.02     | With Load Break Switch                                                                                                                                                                                                            | 8535 | 18% |
| 579 | 72.03     | 11kV HT Metering Panel 3 CT 3 PT for 3 Phase 4 Wire Metering With Transparent Cover TTB, with 30x8mm Cu Bus bars (HT Metering Box Fabricated out of 3mm MS Sheet duly epoxy powder coated, Without Meter)                         | 8535 | 18% |
| 580 | 72.04     | 11kV HT Metering Panel 3 CT 3 PT for 3 Phase 4 Wire Metering With Transparent Cover TTB, with 30x8mm Cu Bus bars (HT Metering Box Fabricated out of 3mm MS Sheet duly powder coated, With Modem) epoxy powder coated, With Modem) | 8535 | 18% |
| 581 | 72.05     | 0.2 S Class ETV Meter with ABT Feature & DLMS Protocol with ToD for above                                                                                                                                                         | 9028 | 18% |
|     |           |                                                                                                                                                                                                                                   |      |     |
|     | <b>73</b> | <b>UPS on Line</b>                                                                                                                                                                                                                |      |     |
| 582 | 73.01     | 1EVA                                                                                                                                                                                                                              | 8504 | 18% |
| 583 | 73.02     | 5KVA                                                                                                                                                                                                                              | 8504 | 18% |
|     |           |                                                                                                                                                                                                                                   |      |     |
|     | <b>74</b> | <b>Heavy Duty Copper Terminals</b>                                                                                                                                                                                                |      |     |
| 584 | 74.01     | 25 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 585 | 74.02     | 35 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 586 | 74.03     | 50 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 587 | 74.04     | 70 & punt Copper Terminals                                                                                                                                                                                                        | 7415 | 18% |
| 588 | 74.05     | 95 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 589 | 74.06     | 120 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 590 | 74.07     | 150 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 591 | 74.08     | 185 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 592 | 74.09     | 225 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 593 | 74.10     | 240 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 594 | 74.11     | 300 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 595 | 74.12     | 100 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
|     |           |                                                                                                                                                                                                                                   |      |     |
|     | <b>75</b> | <b>Heavy Duty Copper Terminals Long Barrel</b>                                                                                                                                                                                    |      |     |
| 596 | 75.01     | 25 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 597 | 75.02     | 35 Scum Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 598 | 75.03     | 50 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 599 | 75.04     | 70 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 600 | 75.05     | 95 Sqmm Copper Terminals                                                                                                                                                                                                          | 7415 | 18% |
| 601 | 75.06     | 120 Squint Copper Terminals                                                                                                                                                                                                       | 7415 | 18% |
| 602 | 75.07     | 150 Squint Copper Terminals                                                                                                                                                                                                       | 7415 | 18% |
| 603 | 75.08     | 185 Squint Copper Terminals                                                                                                                                                                                                       | 7415 | 18% |
| 604 | 75.09     | 225 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 605 | 75.10     | 240 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 606 | 75.11     | 300 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
| 607 | 75.12     | 400 Sqmm Copper Terminals                                                                                                                                                                                                         | 7415 | 18% |
|     |           |                                                                                                                                                                                                                                   |      |     |
|     | <b>76</b> | <b>Al End Terminals (Lugs)</b>                                                                                                                                                                                                    |      |     |
| 608 | 76.01     | 10 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 609 | 76.02     | 16 Squint                                                                                                                                                                                                                         | 8536 | 18% |
| 610 | 76.03     | 25 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 611 | 76.04     | 32 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 612 | 76.05     | 50 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 613 | 76.06     | 70 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 614 | 76.07     | 95 Sqmm                                                                                                                                                                                                                           | 8536 | 18% |
| 615 | 76.08     | 120 Sqmm                                                                                                                                                                                                                          | 8536 | 18% |

|     |       |                                                                                                                                 |      |     |
|-----|-------|---------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 616 | 76.09 | 150 Sqmm                                                                                                                        | 8536 | 18% |
| 617 | 76.10 | 185 Sqmm                                                                                                                        | 8536 | 18% |
| 618 | 76.11 | 225 Sqmm                                                                                                                        | 8536 | 18% |
| 619 | 76.12 | 240 Sqmm                                                                                                                        | 8536 | 18% |
| 620 | 76.13 | 300 Sqmm                                                                                                                        | 8536 | 18% |
| 621 | 76.14 | 400 Sqmm                                                                                                                        | 8536 | 18% |
|     |       |                                                                                                                                 |      |     |
|     |       | <b>77 TOOLS AND PLANT</b>                                                                                                       |      |     |
| 622 | 77.01 | Battery Hydrometer                                                                                                              | 9025 | 18% |
| 623 | 77.02 | Multimeter Electronic Type                                                                                                      | 9030 | 18% |
| 624 | 77.03 | Multimeter Electromechanical Type                                                                                               | 9030 | 18% |
| 625 | 77.04 | Rubber Hand gloves 15kV, SEAMLESS Confirming to ISS (Sample to be verified for seamless before approval) for electrical purpose | 4015 | 18% |
| 626 | 77.05 | Thermometer (Wall Mounted)                                                                                                      | 9025 | 18% |
| 627 | 77.06 | Portable Drilling Machine                                                                                                       | 8459 | 18% |
| 628 | 77.07 | Megger 500 V                                                                                                                    | 8207 | 18% |
| 629 | 77.08 | Megger 2.5kV - 5kV                                                                                                              | 8207 | 18% |
| 630 | 77.09 | Silica Gel                                                                                                                      | 3824 | 18% |
| 631 | 77.10 | Grounding Sticks/Rods (Earthing Rods)                                                                                           | 7215 | 18% |
| 632 | 77.11 | Telescopic Earthing Rods                                                                                                        | 7215 | 18% |
| 633 | 77.12 | Panel Indication Lamps                                                                                                          | 8531 | 28% |
| 634 | 77.13 | Ring Spanners                                                                                                                   | 8207 | 18% |
| 635 | 77.14 | Tube Spanners                                                                                                                   | 8207 | 18% |
| 636 | 77.15 | Pipe Wrench 24 Inches Size                                                                                                      | 8207 | 18% |
| 637 | 77.16 | Pipe Wrench 18 Inches Size                                                                                                      | 8207 | 18% |
| 638 | 77.17 | Double End Spanner                                                                                                              | 8207 | 18% |
| 639 | 77.18 | Hack Saw Frames + B185                                                                                                          | 8207 | 18% |
| 640 | 77.19 | Hand Torch 5 Celled                                                                                                             | 8513 | 28% |
| 641 | 77.20 | Hand Torch 3 Celled                                                                                                             | 8513 | 28% |
| 642 | 77.21 | Rechargable LED Hand Torch                                                                                                      | 8513 | 28% |
| 643 | 77.22 | Portable Inflatable Emergency Lighting System                                                                                   | 8513 | 28% |
| 644 | 77.23 | Insulated cutting pilers 12 inches size                                                                                         | 8203 | 18% |
| 645 | 77.24 | Insulated cutting pilers 8 inches size                                                                                          | 8203 | 18% |
| 646 | 77.25 | Live Line Tester (HT)                                                                                                           | 9024 | 18% |
| 647 | 77.26 | LT Line Tester                                                                                                                  | 9024 | 18% |
| 648 | 77.27 | High Voltage Detector                                                                                                           | 9024 | 18% |
| 649 | 77.28 | Screw driver 18 Inches Size                                                                                                     | 8207 | 18% |
| 650 | 77.29 | Screw driver 12 Inches Size                                                                                                     | 8207 | 18% |
| 651 | 77.30 | Screw driver 8 Inches Size                                                                                                      | 8207 | 18% |
| 652 | 77.31 | Hammer 8 Lbs                                                                                                                    | 8205 | 18% |
| 653 | 77.32 | Hammer 2 Lbs                                                                                                                    | 8205 | 18% |
| 654 | 77.33 | Allen Keys                                                                                                                      | 8204 | 18% |
| 655 | 77.34 | Adjustabale Screw Spanner 8 Inches                                                                                              | 8204 | 18% |
| 656 | 77.35 | Adjustabale Screw Spanner 12 Inches                                                                                             | 8204 | 18% |
| 657 | 77.36 | Box Spanners                                                                                                                    | 8204 | 18% |
| 658 | 77.37 | Transil Oil Dielectric Breakdown Test Kit                                                                                       | 9024 | 18% |
| 659 | 77.38 | SF6 Gas Leak Detector                                                                                                           | 8543 | 18% |
| 660 | 77.39 | DC Volt Meter Range - 3V to +5V                                                                                                 | 9030 | 18% |
| 661 | 77.40 | Hydrometer svrings suitable for vent holes                                                                                      | 9033 | 18% |
| 662 | 77.41 | Specific Gravity Coaaection Chart                                                                                               | 4911 | 12% |
| 663 | 77.42 | Wall Mounting Type Holder for Hydrometer                                                                                        | 9033 | 18% |
| 664 | 77.43 | Earth Resistance Tester                                                                                                         | 9030 | 18% |
| 665 | 77.44 | Rubber Aprron                                                                                                                   | 4015 | 18% |
| 666 | 77.45 | Pipette                                                                                                                         | 7017 | 18% |
| 667 | 77.46 | Protective Goggle                                                                                                               | 9004 | 28% |
| 668 | 77.47 | Acid Resisting jars (4 Pint capacity)                                                                                           | 7010 | 18% |
| 669 | 77.48 | Rain Coats with Hoods                                                                                                           | 6201 | 5%  |
| 670 | 77.49 | Rubber Shoes Knee Height                                                                                                        | 6403 | 12% |
| 671 | 77.50 | Glass Funnel                                                                                                                    | 7017 | 18% |

|     |       |                                                                                                                                                         |      |     |
|-----|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 672 | 77.51 | Hickery Rods                                                                                                                                            | 7227 | 18% |
| 673 | 77.52 | Manilla Rope 1"                                                                                                                                         | 5608 | 12% |
| 674 | 77.53 | Manilla Rope 3/4"                                                                                                                                       | 5608 | 12% |
| 675 | 77.54 | Polypropylene Rope of 26mm dia                                                                                                                          | 5607 | 12% |
| 676 | 77.55 | Files of sizes                                                                                                                                          | 8203 | 18% |
| 677 | 77.56 | Safety Belts                                                                                                                                            | 4015 | 18% |
| 678 | 77.57 | Safety Belts with Accessories                                                                                                                           | 4015 | 18% |
| 679 | 77.58 | Safety Helmets                                                                                                                                          | 6506 | 18% |
| 680 | 77.59 | Electrical Safety (FRP) Helmets attached with electronic induction tester (FRP)                                                                         | 6506 | 18% |
| 681 | 77.60 | Hand Operated Crimping tool 25 Sqmm to 400 Sqmm                                                                                                         | 8203 | 18% |
| 682 | 77.61 | Common Meter Reading Instrument                                                                                                                         | 9026 | 18% |
| 683 | 77.62 | Thermal Imaging Camera                                                                                                                                  | 9031 | 18% |
| 684 | 77.63 | Hydraulic Crimping Tool with suitable Dies for crimping lugs of size upto 400Sqmm                                                                       | 8203 | 18% |
| 685 | 77.64 | Hi Visibility Reflective Jackets                                                                                                                        | 6207 | 5%  |
| 686 | 77.65 | Hi Visibility Reflective Rain Wear                                                                                                                      | 6201 | 12% |
| 687 | 77.66 | Protective Eye Wear for Safety with integral hands free LED Lighting                                                                                    | 9004 | 28% |
| 688 | 77.67 | Leather Shoes                                                                                                                                           | 6403 | 18% |
| 689 | 77.68 | Socks                                                                                                                                                   | 6217 | 5%  |
| 690 | 77.69 | Safety shoes with socks                                                                                                                                 | 6403 | 18% |
| 691 | 77.70 | Waist Leather Belt                                                                                                                                      | 4203 | 28% |
| 692 | 77.71 | Chain saw (Motorised), extremely robust and long lasting chain saw. Highly suitable for cutting firewood, thinning shrubs and bushes and shaping trees. | 8467 | 18% |
| 693 | 77.72 | FRP wall extension ladder                                                                                                                               | 3926 | 28% |
| 694 | 77.73 | Search Lights (Hand Held & Fixable to Vehicle)                                                                                                          | 9405 | 28% |
| 695 | 77.74 | LDPE Safety Cone with ESCOMs Logo                                                                                                                       | 3923 | 18% |
| 696 | 77.75 | HM HOPE Flexible Poly Film Barricade Tape of 50 Microns with ESCOMs Logo, Caution, Danger &                                                             | 3923 | 18% |
| 697 | 77.76 | Men at work Sign Board                                                                                                                                  | 8310 | 28% |
| 698 | 77.77 | Insulated Crowbars                                                                                                                                      | 8544 | 28% |
| 699 | 77.78 | Helmet with Miner Light                                                                                                                                 | 6506 | 18% |
| 700 | 77.79 | Foldable Insulated Fibre Ladder                                                                                                                         | 3926 | 28% |
| 701 | 77.80 | Head Torch                                                                                                                                              | 8513 | 28% |
| 702 | 77.81 | Insulated GOS Operating Handle/Rod for Redesigned & Modified GOS                                                                                        | 7228 | 18% |
|     |       |                                                                                                                                                         |      |     |
|     |       | <b>78 Miscellaneous Materials.</b>                                                                                                                      |      |     |
| 703 | 78.01 | Cable Covering Tiles 125x250x40 mm                                                                                                                      | 6908 | 28% |
| 704 | 78.02 | Cable Covering Tiles 125x125x40 mm                                                                                                                      | 6908 | 28% |
| 705 | 78.03 | RCC Hume Pipes 2000mm long 150mm dia                                                                                                                    | 6810 | 28% |
| 706 | 78.04 | RCC Flume Pipes 2000mm long 200mm dia                                                                                                                   | 6810 | 28% |
| 707 | 78.05 | Collars for RCC hume pipe 150mm dia                                                                                                                     | 6810 | 28% |
| 708 | 78.06 | Collars for RCC hume pipe 200mm dia                                                                                                                     | 6810 | 28% |
| 709 | 78.07 | MS Pipe 200mm dia with collars                                                                                                                          | 7304 | 18% |
| 710 | 78.08 | Burnt Bricks (class 35 modular)                                                                                                                         | 6902 | 18% |
| 711 | 78.09 | Wire cut bricks (Class 75 Modular)                                                                                                                      | 6902 | 18% |
| 712 | 78.10 | Pre - cast hollow blocks (40x20x20 cms) grade 30                                                                                                        | 6810 | 28% |
| 713 | 78.11 | River Sand                                                                                                                                              | 2505 | 5%  |
| 714 | 78.12 | Artificial Sand/Manufacture Sand                                                                                                                        | 2505 | 5%  |
| 715 | 78.13 | Cement in 50kg bags                                                                                                                                     | 2523 | 28% |
| 716 | 78.14 | Ready Mix concrete M20 (1:1.5:3)                                                                                                                        | 3824 | 18% |

|     |       |                                                                                                                       |      |     |
|-----|-------|-----------------------------------------------------------------------------------------------------------------------|------|-----|
| 717 | 78.15 | Ready Mix concrete M25 (1:1:2)                                                                                        | 3824 | 18% |
| 718 | 78.16 | Spall (Jelly used for packing)                                                                                        | 2517 | 5%  |
| 719 | 78.17 | Stone Spans                                                                                                           | 2517 | 5%  |
| 720 | 78.18 | Stone Boulders                                                                                                        | 2517 | 5%  |
| 721 | 78.19 | Route & Joint indicating stone with MS Anchor rod                                                                     | 2517 | 5%  |
| 722 | 78.20 | Black Cambric tape 25 mm wide 10mil thick and in rolls of 50 Mtr                                                      | 5901 | 12% |
| 723 | 78.21 | Yellow Cambric tape 25 mm wide 7mil thick and in rolls of 50 Mtr                                                      | 5901 | 12% |
| 724 | 78.22 | PVC Insulation Tapes 19 mm wide and in rolls of 10 Mtrs                                                               | 8547 | 28% |
| 725 | 78.23 | ACB Paint                                                                                                             | 3210 | 28% |
| 726 | 78.24 | Aluminium Paint                                                                                                       | 3210 | 28% |
| 727 | 78.25 | Grey Enamel Paint smoke/battle ship                                                                                   | 3210 | 28% |
| 728 | 78.26 | Red Oxide Paint                                                                                                       | 3210 | 28% |
| 729 | 78.27 | Cotton Tapes 19 mm wide and in rolls of 50 Mtrs                                                                       | 5808 | 12% |
| 730 | 78.28 | Cotton Waste                                                                                                          | 5202 | 5%  |
| 731 | 78.29 | Hack saw blade 300x12.5 mm                                                                                            | 8208 | 18% |
| 732 | 78.30 | TW plate 300x300x25 mm with 20mm dia holes at the corners and coated with two coats of varnish on one side/SMC board. | 7208 | 18% |
| 733 | 78.31 | TW Meter Board, 300x300x75mm, coated with varnish/SMC board                                                           | 7208 | 18% |
| 734 | 78.32 | Monoplast                                                                                                             | 3920 | 18% |
| 735 | 78.33 | Bitumen Compound                                                                                                      | 2714 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>79 Copper Control cables Li kV Class</b>                                                                           |      |     |
| 736 | 79.01 | 2 Core, 2.5 Sqmm                                                                                                      | 8544 | 28% |
| 737 | 79.02 | 4 Core, 2.5 Sqmm                                                                                                      | 8544 | 28% |
| 738 | 79.03 | 10 Core, 2.5 Sqmm                                                                                                     | 8544 | 28% |
| 739 | 79.04 | 14 Core, 2.5 Sqmm                                                                                                     | 8544 | 28% |
| 740 | 79.05 | 19 Core, 2.5 Sqmm                                                                                                     | 8544 | 28% |
| 741 | 79.06 | 2 Core, 4 Sqmm                                                                                                        | 8544 | 28% |
| 742 | 79.07 | 2 Core, 6 Sqmm                                                                                                        | 8544 | 28% |
| 743 | 79.08 | 2 Core, 10 Sqmm                                                                                                       | 8544 | 28% |
| 741 | 79.09 | 4 Core, 4 Sqmm                                                                                                        | 8544 | 28% |
| 745 | 79.10 | 4 Core, 6 Swum                                                                                                        | 8544 | 28% |
| 746 | 79.11 | 4 Core, 10 Sqmm                                                                                                       | 8544 | 28% |
| 747 | 79.12 | 4 Core, 16 Sqmm                                                                                                       | 8544 | 28% |
| 748 | 79.13 | Fluorent Light Fitting                                                                                                | 8539 | 28% |
| 749 | 79.14 | Fluorent tube                                                                                                         | 8539 | 28% |
| 750 | 79.15 | T-5 Tubelight fitting Complete 28 watts with tube -4 feet                                                             | 8539 | 28% |
| 751 | 79.16 | Florescent Lamp for above                                                                                             | 8539 | 28% |
| 752 | 79.17 | T-5 Tubelight Fitting Complete 14 watts with tube - 2 feet                                                            | 8539 | 28% |
| 753 | 79.18 | Florescent Lamp for above                                                                                             | 8539 | 28% |
| 754 | 79.19 | Sodium Vapour Lamp (250W)                                                                                             | 8539 | 28% |
| 755 | 79.20 | Automatic Switches for Street Lights                                                                                  | 8539 | 28% |
| 756 | 79.21 | GI Bracket for Fluorent Tube                                                                                          | 8539 | 28% |
| 757 | 79.22 | Sodium Vapour lamp Ignitors                                                                                           | 8539 | 28% |
| 758 | 79.23 | Caution/Danger Board                                                                                                  | 9405 | 28% |
| 759 | 79.24 | Standard Torch Cell 1.5V                                                                                              | 8506 | 28% |
| 760 | 79.25 | Street light metering box made of MS sheet steel                                                                      | 8535 | 18% |
| 761 | 79.26 | Street light metering box made of SMC                                                                                 | 8535 | 18% |
|     |       |                                                                                                                       |      |     |
|     |       | <b>80 Compact Fluorescent Lamps</b>                                                                                   |      |     |
| 762 | 80.01 | 5 Watts                                                                                                               | 8539 | 28% |
| 763 | 80.02 | 8 Watts                                                                                                               | 8539 | 28% |
| 764 | 80.03 | 11 Watts                                                                                                              | 8539 | 28% |
| 765 | 80.04 | 14 Watts                                                                                                              | 8539 | 28% |

|     |       |                                                                                                                                                                               |      |     |
|-----|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 766 | 80.05 | 18 Watts                                                                                                                                                                      | 8539 | 28% |
| 767 | 80.06 | 23 Watts                                                                                                                                                                      | 8539 | 28% |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>81 Bolts &amp; Nuts MS</b>                                                                                                                                                 |      |     |
| 768 | 81.01 | B & N Size 16x40mm                                                                                                                                                            | 7318 | 18% |
| 769 | 81.02 | B & N Size 16x50mm                                                                                                                                                            | 7318 | 18% |
| 770 | 81.03 | B & N Size 16x65mm                                                                                                                                                            | 7318 | 18% |
| 771 | 81.04 | B & N Size 16x75mm                                                                                                                                                            | 7318 | 18% |
| 772 | 81.05 | B & N Size 16x85mm                                                                                                                                                            | 7318 | 18% |
| 773 | 81.06 | B & N Size 16x100mm                                                                                                                                                           | 7318 | 18% |
| 774 | 81.07 | B & N Size 16x125mm                                                                                                                                                           | 7318 | 18% |
| 775 | 81.08 | 13 & N Size 16x150mm                                                                                                                                                          | 7318 | 18% |
| 776 | 81.09 | B & N Size 16x175mm                                                                                                                                                           | 7318 | 18% |
| 777 | 81.10 | B & N Size 16x200mm                                                                                                                                                           | 7318 | 18% |
| 778 | 81.11 | B & N Size 16x225mm                                                                                                                                                           | 7318 | 18% |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>GI</b>                                                                                                                                                                     |      |     |
| 779 | 81.12 | B & N Size 16x40mm                                                                                                                                                            | 7318 | 18% |
| 780 | 81.13 | B & N Size 16x50mm                                                                                                                                                            | 7318 | 18% |
| 781 | 81.14 | B & N Size 16x65mm                                                                                                                                                            | 7318 | 18% |
| 782 | 81.15 | B & N Size 16x75mm                                                                                                                                                            | 7318 | 18% |
| 783 | 81.16 | B & N Size 16x85mm                                                                                                                                                            | 7318 | 18% |
| 784 | 81.17 | B & N Size 16x100mm                                                                                                                                                           | 7318 | 18% |
| 785 | 81.18 | B & N Size 16x125mm                                                                                                                                                           | 7318 | 18% |
| 786 | 81.19 | B & N Size 16x150mm                                                                                                                                                           | 7318 | 18% |
| 787 | 81.20 | B & N Size 16x175mm                                                                                                                                                           | 7318 | 18% |
| 788 | 81.21 | B & N Size 16x200mm                                                                                                                                                           | 7318 | 18% |
| 789 | 81.22 | B & N Size 16x225mm                                                                                                                                                           | 7318 | 18% |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>LT Brass Terminal Connector for Transformer (630 Amps, 82 Aprox.Weight 0.790kg)</b>                                                                                        |      |     |
| 780 | 82.01 | 250 kVA                                                                                                                                                                       | 8535 | 18% |
| 781 | 82.02 | 500 kVA                                                                                                                                                                       | 8535 | 18% |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>83 Brass Cable Glands</b>                                                                                                                                                  |      |     |
| 782 | 83.01 | 25mm                                                                                                                                                                          | 8535 | 18% |
| 783 | 83.02 | 32mm                                                                                                                                                                          | 8535 | 18% |
| 784 | 83.03 | 40mm                                                                                                                                                                          | 8535 | 18% |
| 785 | 83.04 | 45mm                                                                                                                                                                          | 8535 | 18% |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>LT Capacitor 3 Ph Housed in a enclosure with necessary fuses, wiring, mounting arrangement as per tech 84 Spec</b>                                                         |      |     |
| 786 | 84.01 | 3 kVAr                                                                                                                                                                        | 8532 | 18% |
| 787 | 84.02 | 9 kVAr                                                                                                                                                                        | 8532 | 18% |
| 788 | 84.03 | 18 kVAr                                                                                                                                                                       | 8532 | 18% |
| 789 | 84.04 | 27 kVAr                                                                                                                                                                       | 8532 | 18% |
| 790 | 84.05 | 54 kVAr                                                                                                                                                                       | 8532 | 18% |
|     |       |                                                                                                                                                                               |      |     |
|     |       |                                                                                                                                                                               |      |     |
|     |       | <b>85 Box for housing the ETV Meter 3 phase 4 wire 5A, with associated LT CTs class 0.5 accuracy, ring type, with wiring clamps, B85N and all other accessories required.</b> |      |     |
| 791 | 85.01 | With CT Ratio 50/5 for 15/25kVA Distribution Transformer Centre                                                                                                               | 7208 | 18% |
| 792 | 85.02 | With CT Ratio 100/5 for 50/63kVA Distribution Transformer Centre                                                                                                              | 7208 | 18% |
| 793 | 85.03 | With CT Ratio 150/5 for 100kVA Distribution Transformer Centre                                                                                                                | 7208 | 18% |
| 794 | 85.04 | With CT Ratio 400/5 for 250kVA Distribution Transformer Centre                                                                                                                | 7208 | 18% |

|     |       |                                                                                                                                                                               |      |     |
|-----|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----|
| 795 | 85.05 | With CT Ratio 800/5 for 500kVA<br>Distribution Transformer Centre                                                                                                             | 7208 | 18% |
|     |       | <b>SMC metering box as above</b>                                                                                                                                              |      |     |
| 796 | 85.06 | With CT Ratio 50/5 for 15/25kVA<br>Distribution Transformer Centre                                                                                                            | 7208 | 18% |
| 797 | 85.07 | With CT Ratio 100/5 for 50/63kVA<br>Distribution Transformer Centre                                                                                                           | 7208 | 18% |
| 798 | 85.08 | With CT Ratio 150/5 for 100kVA<br>Distribution Transformer Centre                                                                                                             | 7208 | 18% |
| 799 | 85.09 | With CT Ratio 400/5 for 250kVA<br>Distribution Transformer Centre                                                                                                             | 7208 | 18% |
| 800 | 85.10 | With CT Ratio 800/5 for 500kVA<br>Distribution Transformer Centre                                                                                                             | 7208 | 18% |
|     |       | <b>Installing RLMU for the Existing<br/>86 Distribution Transformer Center</b>                                                                                                |      |     |
| 801 | 86.01 | Providing RLM Unit with necessary<br>wiring for housing PLC, MCCB, MCB,<br>Energy Meter, CTs, Cotactors etc., as per<br>specification in Metallic Enclosure                   | 8535 | 18% |
| 802 | 86.02 | Programmable Logic Controllers with<br>communication ports                                                                                                                    | 8535 | 18% |
| 803 | 86.03 | GSM Modem                                                                                                                                                                     | 8535 | 18% |
|     |       | <b>MCCB</b>                                                                                                                                                                   |      |     |
| 804 | 86.04 | For 25 kVA, 40/60 Amps                                                                                                                                                        | 8535 | 18% |
| 805 | 86.05 | For 63 kVA, 100 Amps                                                                                                                                                          | 8535 | 18% |
| 806 | 86.06 | For 100 kVA, 160 Amps                                                                                                                                                         | 8535 | 18% |
| 807 | 86.07 | For 100 kVA, 250 Amps                                                                                                                                                         | 8535 | 18% |
| 808 | 86.08 | For 250 kVA, 400 Amps                                                                                                                                                         | 8535 | 18% |
| 809 | 86.09 | For 500 kVA, 630 Amps                                                                                                                                                         | 8535 | 18% |
| 810 | 86.10 | MCE 6 Amps                                                                                                                                                                    | 8535 | 18% |
|     |       | <b>Contactors</b>                                                                                                                                                             |      |     |
| 811 | 86.11 | For 25 kVA, 40 Amps                                                                                                                                                           | 8535 | 18% |
| 812 | 86.12 | For 63 kVA, 100 Amps                                                                                                                                                          | 8535 | 18% |
| 813 | 86.13 | For 100 kVA, 160 Amps                                                                                                                                                         | 8535 | 18% |
| 814 | 86.14 | For 100 kVA, 225 Amps                                                                                                                                                         | 8535 | 18% |
|     |       | <b>Compact Pre - fabricated Packaged<br/>87 Sub station 11 kV/ 433 V</b>                                                                                                      |      |     |
|     |       | <b>Packaged Sub - Station 11kv/433V consisting of 3 way<br/>SF6/VCB insulated compact RMU, oil cooled/dry type<br/>copper wound transformer and L.T. section with one ACB</b> |      |     |
| 815 | 87.01 | With 100 kVA Oil Cooled Transformer                                                                                                                                           | 8504 | 18% |
| 816 | 87.02 | With 250 kVA Oil Cooled Transformer                                                                                                                                           | 8504 | 18% |
| 817 | 87.03 | With 500 kVA Oil Cooled Transformer                                                                                                                                           | 8504 | 18% |
| 818 | 87.04 | With 750 kVA Oil Cooled Transformer                                                                                                                                           | 8504 | 18% |
| 819 | 87.05 | With 990 kVA Oil Cooled Transformer                                                                                                                                           | 8504 | 18% |
| 820 | 87.06 | With 100 kVA Dry Type Transformer                                                                                                                                             | 8504 | 18% |
| 821 | 87.07 | With 250 kVA Dry Type Transformer                                                                                                                                             | 8504 | 18% |
| 822 | 87.08 | With 500 kVA Dry Type Transformer                                                                                                                                             | 8504 | 18% |
| 823 | 87.09 | With 750 kVA Dry Type Transformer                                                                                                                                             | 8504 | 18% |
| 824 | 87.10 | With 990 kVA Dry Type Transformer                                                                                                                                             | 8504 | 18% |
|     | 87.11 | <b>Breakup prices</b>                                                                                                                                                         |      |     |
|     |       | <b>Copper wound Oil Cooled<br/>Distribution Transformer</b>                                                                                                                   |      |     |
| 825 | 87.12 | 500 kVA                                                                                                                                                                       | 8504 | 18% |
| 826 | 87.13 | 750 kVA                                                                                                                                                                       | 8504 | 18% |
| 827 | 87.14 | 990 kVA                                                                                                                                                                       | 8504 | 18% |
| 828 | 87.15 | LT ACB 2000A                                                                                                                                                                  | 8504 | 18% |
| 829 | 87.16 | MCCB 400A                                                                                                                                                                     | 8504 | 18% |



| <b>85 SCRAP MATERIALS</b>                                                                                                                                                         |       |                                                                           |      |     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------------------------------------------------------------------------|------|-----|
| <b>Note: The rates are indicative and the respective zones are authorized to fix the floor price suitably as approved in the Common SR 2012-13 meeting held on 09.11.2012 and</b> |       |                                                                           |      |     |
| 830                                                                                                                                                                               | 85.01 | Copper Wire                                                               | 7408 | 18% |
| 831                                                                                                                                                                               | 85.02 | Released Copper winding released from failed distribution transformers    | 7408 | 18% |
| 832                                                                                                                                                                               | 85.03 | Copper Conductor                                                          | 7408 | 18% |
| 833                                                                                                                                                                               | 85.04 | Copper Ingots                                                             | 7407 | 18% |
| 834                                                                                                                                                                               | 85.05 | Copper Cable with Leads                                                   | 7408 | 18% |
| 835                                                                                                                                                                               | 85.06 | Aluminium                                                                 | 7605 | 18% |
| 836                                                                                                                                                                               | 85.07 | Aluminium wire in pieces                                                  | 7605 | 18% |
| 837                                                                                                                                                                               | 85.08 | ACSR Conductor in Rings/Coils                                             | 7604 | 18% |
| 838                                                                                                                                                                               | 85.09 | Released Aluminium winding released from failed distribution transformers | 7604 | 18% |
| 839                                                                                                                                                                               | 85.10 | Scrap HT/LT Aluminium Winding                                             | 7602 | 18% |
| 840                                                                                                                                                                               | 85.11 | ACSR Conductor                                                            | 7604 | 18% |
| 841                                                                                                                                                                               | 85.12 | Aluminium UG cable                                                        | 7605 | 18% |
| 842                                                                                                                                                                               | 85.13 | Scrap Al Released From UG Cable                                           | 7602 | 18% |
| <b>Iron Items</b>                                                                                                                                                                 |       |                                                                           |      |     |
| 843                                                                                                                                                                               | 85.14 | a) SM Rail Pole, I beam                                                   | 7306 | 18% |
| 844                                                                                                                                                                               | 85.15 | b) Ladder Pole, Tower Parts, Tubular Poles                                | 7306 | 18% |
| 845                                                                                                                                                                               | 85.16 | c) Cross arms, Claraps etc                                                | 7306 | 18% |
| 846                                                                                                                                                                               | 85.17 | d) Released steel from RCC Poles (Skeleton rods)                          | 7306 | 18% |
| 817                                                                                                                                                                               | 85.18 | e) Barbed/Ground wire/Zinc sheet etc                                      | 7313 | 18% |
| 848                                                                                                                                                                               | 85.19 | Transformer Empty tanks of different capacity                             | 7309 | 18% |
| 849                                                                                                                                                                               | 85.20 | Transformer Empty tanks of different capacity                             | 7309 | 18% |
| 850                                                                                                                                                                               | 85.21 | Scrap DOS with Insulators                                                 | 7204 | 18% |
| 851                                                                                                                                                                               | 85.22 | Broken Steel Furniture                                                    | 7204 | 18% |
| 852                                                                                                                                                                               | 85.23 | Brass                                                                     | 7204 | 18% |
| 853                                                                                                                                                                               | 85.21 | Baliga Poles                                                              | 7204 | 18% |
| 854                                                                                                                                                                               | 85.25 | Scrap Wooden Furniture                                                    | 4401 | 12% |
| 855                                                                                                                                                                               | 85.26 | Empty Barrel of 210 Litres Capacity - Good                                | 7310 | 18% |
| 856                                                                                                                                                                               | 85.27 | Empty Barrel of 210 Litres Capacity - Bad                                 | 7310 | 18% |
| 857                                                                                                                                                                               | 85.28 | Lead                                                                      | 7802 | 18% |
| 858                                                                                                                                                                               | 85.29 | HT Metering Cubicle, Distribution Boxes, Feeder Puller Boxes etc          | 7204 | 18% |
| 859                                                                                                                                                                               | 85.30 | Energy Meters (Electro Mech) Single Phase                                 | 7204 | 18% |
| 860                                                                                                                                                                               | 85.31 | Energy Meters (Electro Mech) 3 Phase                                      | 7204 | 18% |
| 861                                                                                                                                                                               | 85.32 | Single/3 Phase Electronic Meters                                          | 7204 | 18% |
| 862                                                                                                                                                                               | 85.33 | CTs & PTs                                                                 | 7204 | 18% |
| <b>Scrap Distribution Transformer of Aluminium Winding (without oil)</b>                                                                                                          |       |                                                                           |      |     |
| 863                                                                                                                                                                               | 85.34 | 15 kVA                                                                    | 8504 | 18% |
| 864                                                                                                                                                                               | 85.35 | 25 kVA                                                                    | 8504 | 18% |
| 865                                                                                                                                                                               | 85.36 | 63 kVA                                                                    | 8504 | 18% |
| 866                                                                                                                                                                               | 85.37 | 100 kVA                                                                   | 8504 | 18% |
| 867                                                                                                                                                                               | 85.38 | 200 kVA                                                                   | 8504 | 18% |
| 868                                                                                                                                                                               | 85.39 | 250 kVA                                                                   | 8504 | 18% |
| 869                                                                                                                                                                               | 85.40 | 300 kVA                                                                   | 8504 | 18% |
| 870                                                                                                                                                                               | 85.41 | 500 kVA                                                                   | 8504 | 18% |
| <b>Scrap Distribution Transformer of Copper Winding (without oil)</b>                                                                                                             |       |                                                                           |      |     |
| 871                                                                                                                                                                               | 85.42 | 15 kVA                                                                    | 8504 | 18% |
| 872                                                                                                                                                                               | 85.43 | 25 kVA                                                                    | 8504 | 18% |

|     |       |                                                                                       |      |     |
|-----|-------|---------------------------------------------------------------------------------------|------|-----|
| 873 | 85.44 | 50 kVA                                                                                | 8504 | 18% |
| 874 | 85.15 | 63 kVA                                                                                | 8504 | 18% |
| 875 | 85.46 | 100 kVA                                                                               | 8504 | 18% |
| 876 | 85.47 | 200 kVA                                                                               | 8504 | 18% |
| 877 | 85.48 | 250 kVA                                                                               | 8504 | 18% |
| 878 | 85.49 | 300 kVA                                                                               | 8504 | 18% |
| 879 | 85.50 | 500 kVA                                                                               | 8504 | 18% |
| 880 | 85.51 | 5 MVA                                                                                 | 8504 | 18% |
|     |       |                                                                                       |      |     |
|     |       | <b>Scrap CSP 11kV Distribution Transformer</b>                                        |      |     |
| 881 | 85.52 | 15 kVA                                                                                | 8504 | 18% |
| 882 | 85.53 | 25 kVA                                                                                | 8504 | 18% |
| 883 | 85.54 | 63 kVA                                                                                | 8504 | 18% |
|     |       |                                                                                       |      |     |
|     |       | <b>Scrap Wooden Reels</b>                                                             |      |     |
| 884 | 85.55 | In good condition                                                                     | 4401 | 12% |
| 885 | 85.56 | Empty Wooden Reel Deteriorated and with iron Rods                                     | 4401 | 12% |
| 886 | 85.57 | Scrap Aluminium Lead Wire                                                             | 7605 | 12% |
| 887 | 85.58 | Scrap RMU with/without breaker(rusted & borken panles)MEI Make borken panles)MEI Make | 7204 | 18% |
| 888 | 85.59 | Scrap RMU with/without breaker(rusted & borken panles)MEI Make                        | 7204 | 18% |

NOTE:- The above rates are subject to change.

If any of the above rates modified by the GST Council, Than revised rates shall be applicable.